

TTA Standard

정보통신단체표준(기술규격)
TTAT.3G-29.514(R15-15.0.0)

제정일: 2018년 9월

3GPP-(Technical Speciation
Group Core Network and
Terminals; 5G System; Policy
Authorization Service; Stage 3)



본 문서에 대한 저작권은 TTA에 있으며, TTA와 사전 협의 없이 이 문서의 전체 또는 일부를 상업적 목적으로 복제 또는 배포해서는 안 됩니다.

Copyright 20xx, Telecommunications Technology Association.
All rights reserved.

3GPP TS 29.514 V15.0.0 (2018-06)

Technical Specification

**3rd Generation Partnership Project;
Technical Specification Group Core Network and Terminals;
5G System; Policy Authorization Service;
Stage 3
(Release 15)**



Keywords

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2018, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
LTE™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
GSM® and the GSM logo are registered and owned by the GSM Association

Contents

Foreword	6
1 Scope	7
2 References	7
3 Definitions and abbreviations.....	8
3.1 Definitions	8
3.2 Abbreviations.....	8
4 Npcf_PolicyAuthorization Service	9
4.1 Service Description.....	9
4.1.1 Overview	9
4.1.2 Service Architecture.....	9
4.1.3 Network Functions	10
4.1.3.1 Policy Control Function (PCF).....	10
4.1.3.2 NF Service Consumers	10
4.2 Service Operations.....	10
4.2.1 Introduction	10
4.2.2 Npcf_PolicyAuthorization_Create service operation.....	11
4.2.2.1 General	11
4.2.2.2 Initial provisioning of service information	11
4.2.2.3 Gate control	14
4.2.2.4 Initial Background Data Transfer policy indication	14
4.2.2.5 Initial provisioning of sponsored connectivity information.....	15
4.2.2.6 Subscriptions to Service Data Flow QoS notification control	16
4.2.2.7 Subscription to Service Data Flow Deactivation	16
4.2.2.8 Initial provisioning of traffic routing information	16
4.2.2.9 Request of access network information	17
4.2.3 Npcf_PolicyAuthorization_Update service operation.....	18
4.2.3.1 General	18
4.2.3.2 Modification of service information.....	18
4.2.3.3 Gate control	20
4.2.3.4 Background Data Transfer policy indication at policy authorization update.....	20
4.2.3.5 Modification of sponsored connectivity information	20
4.2.3.6 Modification of Subscription to Service Data Flow QoS notification control.....	21
4.2.3.7 Modification of Subscription to Service Data Flow Deactivation	22
4.2.3.8 Update of traffic routing information	22
4.2.3.9 Request of access network information	22
4.2.4 Npcf_PolicyAuthorization_Delete service operation.....	23
4.2.4.1 General	23
4.2.4.2 AF application session context termination.....	23
4.2.4.3 Reporting usage for sponsored data connectivity	24
4.2.4.4 Request and report of access network information.....	24
4.2.5 Npcf_PolicyAuthorization_Notify service operation.....	25
4.2.5.1 General	25
4.2.5.2 Notification about application session context event.....	26
4.2.5.3 Notification about application session context termination	27
4.2.5.4 Notification about Service Data Flow QoS notification control.....	27
4.2.5.5 Notification about Service Data Flow Deactivation	28
4.2.5.6 Reporting usage for sponsored data connectivity	28
4.2.5.7 Reporting access network information	29
4.2.6 Npcf_PolicyAuthorization_Subscribe service operation.....	29
4.2.6.1 General	29
4.2.6.2 Handling of subscription to events for the existing application session context	30
4.2.6.3 Initial subscription to events without provisioning of service information	31
4.2.6.4 Subscription to usage monitoring of sponsored data connectivity	33
4.2.6.5 Request of access network information	33
4.2.7 Npcf_PolicyAuthorization_Unsubscribe service operation	34

4.2.7.1	General	34
4.2.7.2	Unsubscription to events	34
5	Npcf_PolicyAuthorization Service API	35
5.1	Introduction	35
5.2	Usage of HTTP	35
5.2.1	General	35
5.2.2	HTTP standard headers	35
5.2.2.1	General	35
5.2.2.2	Content type	35
5.2.3	HTTP custom headers	35
5.3	Resources	36
5.3.1	Resource Structure	36
5.3.2	Resource: Application Sessions (Collection)	36
5.3.2.1	Description	36
5.3.2.2	Resource definition	37
5.3.2.3	Resource Standard Methods	37
5.3.2.3.1	POST	37
5.3.2.4	Resource Custom Operations	37
5.3.3	Resource: Individual Application Session Context (Document)	38
5.3.3.1	Description	38
5.3.3.2	Resource definition	38
5.3.3.3	Resource Standard Methods	38
5.3.3.3.1	GET	38
5.3.3.3.2	PATCH	38
5.3.3.4	Resource Custom Operations	39
5.3.3.4.1	Overview	39
5.3.3.4.2	Operation: delete	39
5.3.3.4.2.1	Description	39
5.3.3.4.2.2	Operation Definition	39
5.3.4	Resource: Events Subscription (Document)	40
5.3.4.1	Description	40
5.3.4.2	Resource definition	40
5.3.4.3	Resource Standard Methods	40
5.3.4.3.1	PUT	40
5.3.4.3.2	DELETE	41
5.3.3.4	Resource Custom Operations	41
5.4	Custom Operations without associated resources	41
5.5	Notifications	42
5.5.1	General	42
5.5.2	Event Notification	42
5.5.2.1	Description	42
5.5.2.2	Target URI	42
5.5.2.3	Standard Methods	42
5.5.2.3.1	POST	42
5.5.3	Termination Request	43
5.5.3.1	Description	43
5.5.3.2	Target URI	43
5.5.3.3	Standard Methods	43
5.5.3.3.1	POST	43
5.6	Data Model	43
5.6.1	General	43
5.6.2	Structured data types	45
5.6.2.1	Introduction	45
5.6.2.2	Type AppSessionContext	46
5.6.2.3	Type AppSessionContextReqData	47
5.6.2.4	Type AppSessionContextRespData	47
5.6.2.5	Type AppSessionContextUpdateData	48
5.6.2.6	Type EventsSubscReqData	48
5.6.2.7	Type MediaComponent	49
5.6.2.8	Type MediaSubComponent	49
5.6.2.9	Type EventsNotification	50

5.6.2.10	Type AfEventSubscription	50
5.6.2.11	Type AfEventNotification	51
5.6.2.12	Type TerminationInfo.....	51
5.6.2.13	Type AfRoutingRequirement	51
5.6.2.14	Type RouteToLocation.....	51
5.6.2.15	Type RouteInformation	52
5.6.2.16	Type SpatialValidity.....	52
5.6.2.17	Type EthFlowDescription.....	52
5.6.2.18	Type AccessNetChargingAddress.....	53
5.6.2.19	Type AccessNetChargingIdentifier	53
5.6.2.20	Type AnGwAddress	53
5.6.2.21	Flows	53
5.6.3	Simple data types and enumerations	53
5.6.3.1	Introduction	53
5.6.3.2	Simple data types.....	54
5.6.3.3	Enumeration: MediaType	54
5.6.3.4	Enumeration: ReservPriority	54
5.6.3.5	Enumeration: ServAuthInfo	55
5.6.3.6	Enumeration: SponsoringStatus.....	55
5.6.3.7	Type AfEvent	55
5.6.3.8	Type AfNotifMethod.....	56
5.6.3.9	Type QosNotifType.....	56
5.6.3.10	Type TerminationCause	56
5.6.3.11	Type RequiredAccessInfo	56
5.7	Error handling	57
5.7.1	General.....	57
5.7.2	Protocol Errors	57
5.7.3	Application Errors.....	57
5.8	Feature negotiation	58
Annex A (normative):	OpenAPI specification.....	59
A.1	General	59
A.2	Npcf_PolicyAuthorization API.....	59
Annex B (informative):	Change history	74

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present specification provides the stage 3 definition of the Policy Authorization Service of the 5G System.

The 5G System Architecture is defined in 3GPP TS 23.501 [2]. The stage 2 definition and related procedures for the Npcf Policy Authorization Service are specified in 3GPP TS 23.502 [3] and 3GPP TS 23.503 [4].

The 5G System stage 3 call flows are provided in 3GPP TS 29.513 [7].

The Technical Realization of the Service Based Architecture and the Principles and Guidelines for Services Definition are specified in 3GPP TS 29.500 [5] and 3GPP TS 29.501 [6].

The Policy Authorization Service is provided by the Policy Control Function (PCF). This service creates policies as requested by the authorised AF for the PDU Session to which the AF session is bound.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.501: "System Architecture for the 5G System; Stage 2".
- [3] 3GPP TS 23.502: "Procedures for the 5G System; Stage 2".
- [4] 3GPP TS 23.503: "Policy and Charging Control Framework for the 5G System; Stage 2".
- [5] 3GPP TS 29.500: "5G System; Technical Realization of Service Based Architecture; Stage 3".
- [6] 3GPP TS 29.501: "5G System; Principles and Guidelines for Services Definition; Stage 3".
- [7] 3GPP TS 29.513: "5G System; Policy and Charging Control signalling flows and QoS parameter mapping; Stage 3".
- [8] 3GPP TS 29.512: "5G System; Session Management Policy Control Service; Stage 3".
- [9] IETF RFC 7540: "Hypertext Transfer Protocol Version 2 (HTTP/2)".
- [10] IETF RFC 8259: "The JavaScript Object Notation (JSON) Data Interchange Format".
- [11] OpenAPI: "OpenAPI 3.0.0 Specification", <https://github.com/OAI/OpenAPI-Specification/blob/master/versions/3.0.0.md>.
- [12] 3GPP TS 29.571: "5G System; Common Data Types for Service Based Interfaces; Stage 3".
- [13] 3GPP TS 29.508: "5G System; Session Management Event Exposure Service; Stage 3".
- [14] 3GPP TS 29.554: "5G System; Background Data Transfer Policy Control Service; Stage 3".
- [15] 3GPP TS 29.122: "T8 reference point for Northbound APIs".
- [16] IEEE 802.3-2015: "IEEE Standard for Ethernet".

- [17] IEEE 802.1Q-2014: "Bridges and Bridged Networks".
- [18] IETF RFC 7042: "IANA Considerations and IETF Protocol and Documentation Usage for IEEE 802 Parameters".
- [19] IETF RFC 3986: "Uniform Resource Identifier (URI): Generic Syntax".
- [20] 3GPP TS 29.214: "Policy and Charging Control over Rx reference point".
- [21] IETF RFC 7386: "JSON Merge Patch".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

Application Function (AF): Element offering application(s) that use PDU session resources.

AF application session context: Application level session context established by an application level signalling protocol offered by the AF that requires a session context set-up with explicit session context description before the use of the service.

PCC rule: Set of information enabling the detection of a service data flow and providing parameters for policy control and/or charging control.

Service information: Set of information conveyed from the AF/NEF to the PCF by the Npcf_PolicyAuthorization service to be used as a basis for PCC decisions at the PCF, including information about the AF/NEF application session context (e.g. application identifier, type of media, bandwidth, IP address and port number).

Service data flow: An aggregate set of packet flows.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

AF	Application Function
DEI	Drop Eligible Indicator
DNAI	DN Access Identifier
DNN	Data Network Name
E-UTRA	Evolved Universal Terrestrial Radio Access
H-PCF	PCF in the HPLMN
JSON	JavaScript Object Notation
NEF	Network Exposure Function
NR	New Radio
PCC	Policy and Charging Control
PCF	Policy Control Function
PCP	Priority Code Point
PRA	Presence Reporting Area
QoS	Quality of Service
RFSP	RAT Frequency Selection Priority
SDF	Service Data Flow
SMF	Session Management Function
S-NSSAI	Single Network Slice Selection Assistance Information
SUPI	Subscription Permanent Identifier
UDR	Unified Data Repository

UPF	User Plane Function
URSP	UE Route Selection Policy
VID	VLAN Identifier
VLAN	Virtual Local Area Network
V-PCF	PCF in the VPLMN

4 Npcf_PolicyAuthorization Service

4.1 Service Description

4.1.1 Overview

The Npcf_PolicyAuthorization Service, as defined in 3GPP TS 23.502 [3] and in 3GPP TS 23.503 [4], is provided by the Policy Control Function (PCF).

The Npcf_PolicyAuthorization service authorises an AF request and creates policies as requested by the authorised NF service consumer for the PDU session to which the AF session is bound to. This service allows the NF service consumer to subscribe/unsubscribe to the notification of events (e.g. Access Type and RAT type, PLMN identifier, access network information, usage report).

4.1.2 Service Architecture

The 5G System Architecture is defined in 3GPP TS 23.501 [2]. The Policy and Charging control related 5G architecture is also described in 3GPP TS 23.503 [4] and 3GPP TS 29.513 [7].

The only known NF service consumers of the Npcf_PolicyAuthorization service are the Application Function (AF) and the Network Exposure Function (NEF).

The Npcf_PolicyAuthorization service is provided by the PCF and consumed by the AF and the NEF, as shown in figure 4.1.2-1 for the SBI representation model and in figure 4.1.2-2 for the reference point representation model.




Figure 4.1.2-1: Npcf_PolicyAuthorization service Architecture, SBI representation




Figure 4.1.2-2: Npcf_PolicyAuthorization service Architecture, reference point representation

The NEF can act as an AF using N5 reference point.

4.1.3 Network Functions

4.1.3.1 Policy Control Function (PCF)

The PCF (Policy Control Function) is a functional element that encompasses policy control decision and flow based charging control functionalities, access and mobility policy decisions for the control of the UE Service Area Restrictions and RAT/RFSP control, and UE Policy for the Access network discovery and selection policy and UE Route Selection Policy (URSP).

The policy control decision and flow based charging control functionalities enable the PCF to provide network control regarding the service data flow detection, gating, QoS and flow based charging (except credit management) towards the SMF/UPF.

The PCF receives session and media related information from the Npcf_PolicyAuthorization service consumers and notifies them of subscribed traffic plane events.

The PCF checks that the service information provided by the NF service consumer is consistent with the operator defined policy rules before storing the service information.

The PCF uses the received service information and the subscription information when it applies as basis for the policy and charging control decisions.

The PCF derives PCC rules and provisions them to the SMF via the Npcf_SMPolicyControl service and subscribes to traffic plane events via the Nsmf_EventExposure service as described in 3GPP TS 29.512 [8].

4.1.3.2 NF Service Consumers

The known NF service consumers are the AF and the NEF, as defined in 3GPP TS 23.502 [3].

The AF is an element offering applications that require the Policy and Charging Control of traffic plane resources. The AF uses the Npcf_PolicyAuthorization service to provide service information to the PCF.

The AFs can be deployed by the same operator offering the access services or can be provided by external third-party service provider. If the AF is not allowed by the operator to access directly the PCF, the AF uses the external exposure framework via NEF to interact with the PCF, as described in subclause 5.20 of 3GPP TS 23.501 [2].

The Network Exposure Function (NEF) supports external exposure of capabilities of network functions.

4.2 Service Operations

4.2.1 Introduction

Service operations defined for the Npcf_PolicyAuthorization Service are shown in table 4.2.1-1.

Table 4.2.1-1: Npcf_PolicyAuthorization Service Operations

Service Operation Name	Description	Initiated by
Npcf_PolicyAuthorization_Create	Determines and installs the policy according to the service information provided by an authorized NF service consumer.	AF, NEF
Npcf_PolicyAuthorization_Update	Determines and updates the policy according to the modified service information provided by an authorized NF service consumer.	AF, NEF
Npcf_PolicyAuthorization_Delete	Provides means to delete the application session context of the NF service consumer.	AF, NEF
Npcf_PolicyAuthorization_Notify	Notifies NF service consumer of the subscribed events.	PCF
Npcf_PolicyAuthorization_Subscribe	Allows NF service consumers to subscribe to the notification of events.	AF, NEF
Npcf_PolicyAuthorization_Unsubscribe	Allows NF service consumers to unsubscribe to the notification of events.	AF, NEF

NOTE: The NEF and the AF use the Npcf_PolicyAuthorization service in the same way. To improve the readability of the service procedures, only the AF is mentioned in the following subclauses.

4.2.2 Npcf_PolicyAuthorization_Create service operation

4.2.2.1 General

The Npcf_PolicyAuthorization_Create service operation authorizes the request from the NF service consumer, and optionally communicates with Npcf_SMPolicyControl service to determine and install the policy according to the information provided by the NF service consumer.

The Npcf_PolicyAuthorization_Create service operation creates an application session context in the PCF.

The following procedures using the Npcf_PolicyAuthorization_Create service operation are supported:

- Initial provisioning of service information.
- Gate control.
- Initial Background Data Transfer policy indication.
- Initial provisioning of sponsored connectivity information.
- Subscription to Service Data Flow QoS notification control.
- Subscription to Service Data Flow Deactivation.
- Initial provisioning of traffic routing information.
- Request of access network information.

4.2.2.2 Initial provisioning of service information

This procedure is used to set up an AF application session context for the service as defined in 3GPP TS 23.501 [2], 3GPP TS 23.502 [3] and 3GPP TS 23.503 [4].

Figure 4.2.2.2-1 illustrates the initial provisioning of service information.




Figure 4.2.2.2-1: Initial provisioning of service information

When a new AF application session context is being established and media information for this application session context is available at the AF and the related media requires PCC control, the AF shall invoke the `Npcf_PolicyAuthorization_Create` service operation by sending the HTTP POST request to the resource URI representing the "Application Sessions" collection resource of the PCF, as shown in figure 4.2.2.2-1, step 1.

The AF shall include in the "AppSessionContext" data type in the payload body of the HTTP POST request a partial representation of the "Individual Application Session Context" resource by providing the "AppSessionContextReqData" data type. The "Individual Application Session Context" resource and the "Events Subscription" sub-resource are created as described below.

The AF shall provide in the body of the HTTP POST request:

- for IP type PDU sessions, the IP address (IPv4 or IPv6) of the UE in the "ueIPv4" or "ueIPv6" attribute; and
- for Ethernet type PDU sessions, the MAC address of the UE in the "ueMac" attribute.

The AF shall provide the corresponding service information in the "medComponents" attribute if available. The AF shall indicate to the PCF as part of the "medComponents" attribute whether the service data flow(s) (IP or Ethernet) should be enabled or disabled with the "fStatus" attribute.

The AF may include the AF application identifier in the "afAppId" attribute into the body of the HTTP POST request in order to indicate the particular service that the AF session belongs to.

The AF application identifier may be provided at both "AppSessionContextReqData" data type level, and "MediaComponent" data type level. When provided at both levels, the AF application identifier provided at "MediaComponent" data type level shall have precedence.

The AF application identifier at the "AppSessionContextReqData" data type level may be used to trigger the PCF to indicate to the SMF/UPF to perform the application detection based on the operator's policy as defined in 3GPP TS 29.512 [8].

The AF may include the AF charging identifier in the "afChargId" attribute for charging correlation purposes.

The AF may also include the "evSubsc" attribute of "EventSubscReqData" data type to request the notification of certain user plane events. The AF shall include the events to subscribe to in the "events" attribute, and the notification URI where to address the `Npcf_PolicyAuthorization_Notify` service operation in the "notifUri" attribute. The events subscription is provisioned in the "Events Subscription" sub-resource.

The AF shall also include the "notifUri" attribute in the "AppSessionContextReqData" data type to indicate the URI where the PCF can request to the AF the deletion of the "Individual Application Session Context" resource.

If the PCF cannot successfully fulfil the received HTTP POST request due to the internal PCF error or due to the error in the HTTP POST request, the PCF shall send the HTTP error response as specified in subclause 5.7.

Otherwise, when the PCF receives the HTTP POST request from the AF, the PCF shall apply session binding as described in 3GPP TS 29.513 [7]. To allow the PCF to identify the PDU session for which the HTTP POST request applies, the AF shall provide in the body of the HTTP POST request:

- for IP type PDU session, either the "ueIpv4" attribute or "ueIpv6" attribute containing the IPv4 or the IPv6 address applicable to an IP flow or IP flows towards the UE; and
- for Ethernet type PDU session, the "ueMac" attribute containing the UE MAC address applicable to an Ethernet flow or Ethernet flows towards the UE.

The AF may provide DNN in the "dnn" attribute, SUPI in the "supi" attribute, the S-NSSAI in the "sliceInfo" attribute, or other information if available.

Editor's note: It is FFS which additional information may be required from the AF for session binding in case of IP overlapping.

If the PCF fails in executing session binding, the PCF shall reject the Npcf_PolicyAuthorization_Create service operation with an HTTP "500 Internal Server Error" response including the "cause" attribute set to "PDU_SESSION_NOT_AVAILABLE".

If the request contains the "medComponents" attribute the PCF shall store the received service information. The PCF shall process the received service information according to the operator policy and may decide whether the request is accepted or not. The PCF may take the priority information within the "resPrio" attribute into account when making this decision.

If the service information provided in the body of the HTTP POST request is rejected (e.g. the subscribed guaranteed bandwidth for a particular user is exceeded), the PCF shall indicate in an HTTP "403 Forbidden" response message the cause for the rejection including the "cause" attribute set to "REQUESTED_SERVICE_NOT_AUTHORIZED". If the service information provided in the HTTP POST request is rejected due to a temporary condition in the network (e.g. the user plane in the cell the user is located is congested), the PCF may include in the "403 Forbidden" response the "cause" attribute set to "REQUESTED_SERVICE_TEMPORARILY_NOT_AUTHORIZED".

To allow the PCF and SMF/UPF to perform PCC rule authorization and QoS flow binding for the described service data flows, the AF shall supply:

- for IP type PDU session, both source and destination IP addresses and port numbers in the "fDescs" attribute within the "medSubComps" attribute, if such information is available; and
- for Ethernet type PDU session, the Ethernet Packet filters in the "ethfDescs" attribute within the "medSubComps" attribute, if such information is available.

The AF may specify the ToS traffic class within the "tosTrCl" attribute for the described service data flows together with the "fDescs" attribute.

The AF may include the "resPrio" attribute at the "AppSessionContextReqData" data type level to assign a priority to the AF Session as well as include the "resPrio" attribute at the "MediaComponent" data type level to assign a priority to the service data flow. The presence of the "resPrio" attribute in both levels does not constitute a conflict as they each represent different types of priority. The reservation priority at the "AppSessionContextReqData" data type level provides the relative priority for an AF session while the reservation priority at the "MediaComponent" data type level provides the relative priority for a service data flow within a session. If the "resPrio" attribute is not specified, the requested priority is PRIO_1.

The PCF shall check whether the received service information requires PCC rules to be created and provisioned as specified in 3GPP TS 29.513 [7]. Provisioning of PCC rules to the SMF shall be carried out as specified at 3GPP TS 29.512 [8].

Based on the received subscription information from the AF, the PCF may create a subscription to event notifications for a related PDU session from the SMF, as described in 3GPP TS 29.512 [8] and 3GPP TS 29.508 [13].

If the PCF created an "Individual Application Session Context" resource, the PCF shall send to the AF a "201 Created" response to the HTTP POST request, as shown in figure 4.2.2.2-1, step 2. The PCF shall include in the "201 Created" response:

- a Location header field; and
- an "AppSessionContext" data type in the payload body.

The Location header field shall contain the URI of the created individual application session context resource i.e. "{apiRoot}/npcf-policyauthorization/v1/app-sessions/{appSessionId}".

When "Events Subscription" sub-resource is created in this procedure, the AF shall build the sub-resource URI by adding the path segment "/events-subscription" at the end of the URI path received in the Location header field.

The "AppSessionContext" data type payload body shall contain the representation of the created "Individual Application Session Context" resource and may include the "Events Subscription" sub-resource.

The PCF shall include in the "EvsNotif" attribute:

- if the AF subscribed to the "CHARGING_CORRELATION" event in the HTTP POST request, the "event" attribute set to "CHARGING_CORRELATION" and the "anChargIds" attribute containing the access network charging identifier(s) and may include the "anChargAddr" attribute containing the access network charging address;
- if the AF subscribed to the event "PLMN_CHG" in the HTTP POST request, the "event" attribute set to "PLMN_CHG" and the "plmnId" attribute including the PLMN identifier if the PCF has previously requested to be updated with this information in the SMF; and
- if the AF subscribed to the event "ACCESS_TYPE_CHG" in the HTTP POST request, the "event" attribute set to "ACCESS_TYPE_CHG" and the attributes "accessType" including the access type, "ratType" including the RAT type when applicable for the notified access type, and the "anGwAddr" including access network gateway address when available, if the PCF has previously requested to be updated with this information in the SMF.

The AF subscription to other specific events using the Npcf_PolicyAuthorization_Create request is described in the related subclauses. Notification of events when the applicable information is not available in the PCF when receiving the Npcf_PolicyAuthorization_Create request is described in subclause 4.2.5.

The acknowledgement towards the AF should take place before or in parallel with any required PCC rule provisioning towards the SMF.

NOTE: The behaviour when the AF does not receive the HTTP response message, or when it arrives after the internal timer waiting for it has expired, or when it arrives with an indication different than a success indication, are outside the scope of this specification and based on operator policy.

4.2.2.3 Gate control

This procedure is used by an AF to instruct the PCF about when the service data flow(s) are to be enabled or disabled for a PDU session.

The AF shall include in the HTTP POST request message described in subclause 4.2.2.2 the "fStatus" attribute for the flows to be enabled or disabled within the "medComponents" or "medSubComponents" attributes.

As result of this action, the PCF shall set the appropriate gate status for the corresponding active PCC rule(s).

The PCF shall reply to the AF as described in subclause 4.2.2.2.

4.2.2.4 Initial Background Data Transfer policy indication

This procedure is used by an AF to indicate a transfer policy negotiated for background data transfer using the Npcf_BDTPolicyControl service as described in 3GPP TS 29.554 [14].

The AF may include in the HTTP POST request message described in subclause 4.2.2.2 a reference identifier related to a transfer policy negotiated for background data transfer in the "bdtRefId" attribute.

NOTE 1: The PCF will retrieve the corresponding transfer policy from the UDR based on the reference identifier within the "bdtRefId" attribute. In case only one PCF is deployed in the network, transfer policies can be locally stored in the PCF and the interaction with the UDR is not required.

If the PCF cannot retrieve the transfer policy, the PCF shall set to TP_NOT_KNOWN the "servAuthInfo" attribute in the HTTP response message to the AF to indicate that the transfer policy is unknown.

If the time window of the received transfer policy has expired, the PCF shall set to TP_EXPIRED the "servAuthInfo" attribute in the HTTP response message to indicate to the AF that the transfer policy has expired. Otherwise, if the time window of the received transfer policy has not yet occurred, the PCF shall set to TP_NOT_YET_OCCURRED the

"servAuthInfo" attribute in the HTTP response message to the AF to indicate that the time window of the transfer policy has not yet occurred.

NOTE 2: In the case that the PCF cannot retrieve the transfer policy, the transfer policy time window has not yet occurred or the transfer policy expired, the PCF makes the decision without considering the transfer policy.

The PCF shall reply to the AF as described in subclause 4.2.2.2.

4.2.2.5 Initial provisioning of sponsored connectivity information

This procedure is used by an AF to indicate sponsored data connectivity when Sponsored Connectivity feature is supported.

The AF shall provide in the "AppSessionContext" data type of the HTTP POST request message described in subclause 4.2.2.2 an application service provider identity and a sponsor identity within the "aspId" attribute and "sponId" attribute. Additionally, the AF may provide an indication to the PCF of sponsored data connectivity not enabled by including the "sponStatus" attribute set to "SPONSOR_DISABLED".

To support the usage monitoring of sponsored data connectivity, the AF may subscribe with the PCF to the notification of usage threshold reached. The AF shall include:

- an entry of the "AfEventSubscription" data type in the "events" attribute with the "event" attribute set to "USAGE_REPORT"; and
- the "usgThres" attribute of "UsageThreshold" data type in the "EventsSubscReqData" data type with:
 - a) the total volume in the "totalVolume" attribute; or
 - b) the uplink volume only in the "uplinkVolume" attribute; or
 - c) the downlink volume only in the "downlinkVolume"; and/or
 - d) the time in the "duration" attribute.

NOTE 1: If the AF is in the user plane, the AF can handle the usage monitoring and therefore it is not required to provide a usage threshold to the PCF as part of the sponsored connectivity functionality.

When the AF indicated to enable sponsored data connectivity, and the UE is roaming in a VPLMN, the following procedures apply:

- If the AF is located in the HPLMN, for home routed roaming case and when the operator policies do not allow accessing the sponsored data connectivity with this roaming case, the H-PCF shall reject the service request and shall include in the HTTP "403 Forbidden" response message the "cause" attribute set to "UNAUTHORIZED_SPONSORED_DATA_CONNECTIVITY".
- If the AF is located in the VPLMN, the V-PCF shall reject the service request and shall include in the HTTP "403 Forbidden" response message the "cause" attribute set to "UNAUTHORIZED_SPONSORED_DATA_CONNECTIVITY".

When the AF indicated to enable sponsored data connectivity, and the UE is non-roaming or roaming with the home routed case and the operator policies allow accessing the sponsored data connectivity with this roaming case, the following procedures apply:

- If the SMF does not support sponsored connectivity and the required reporting level for that service indicates a sponsored connectivity level according to 3GPP TS 29.512 [8], then the PCF shall reject the request and shall include in the HTTP "403 Forbidden" response message the "cause" attribute set to "REQUESTED_SERVICE_NOT_AUTHORIZED".
- If the SMF supports sponsored data connectivity feature or the required reporting level is different from sponsored connectivity level as described in 3GPP TS 29.512 [8], then the PCF, based on operator policies, shall check whether it is required to validate the sponsored connectivity data. If it is required, it shall perform the authorizations based on sponsored data connectivity profiles. If the authorization fails, the PCF shall include in the HTTP "403 Forbidden" response message the "cause" attribute set to "UNAUTHORIZED_SPONSORED_DATA_CONNECTIVITY".

NOTE 2: The PCF is not required to verify that a trust relationship exists between the operator and the sponsors.

The PCF shall reply to the AF as described in subclause 4.2.2.2.

4.2.2.6 Subscriptions to Service Data Flow QoS notification control

The subscription to Service Data Flow QoS notification control is used by an AF to subscribe to receive a notification when the GBR QoS targets for one or more service data flows cannot be fulfilled.

NOTE: It may happen that the GBR QoS targets for one or more PCC rules (i.e. Service Data Flows) cannot be fulfilled, either permanently or temporarily in the radio access network.

The AF shall use the "EventsSubscReqData" data type as described in subclause 4.2.2.2 and shall include in the HTTP POST request message an event within the "evSubsc" attribute with the "event" attribute set to "QOS_NOTIF_CONTROL".

The PCF shall reply to the AF as described in subclause 4.2.2.2.

As result of this action, the PCF shall set the appropriate subscription to QoS notification control for the corresponding PCC rule(s) as described in in 3GPP TS 29.512 [8].

4.2.2.7 Subscription to Service Data Flow Deactivation

This procedure is used by an AF to subscribe to the notification of deactivation of one or more Service Data Flows within the AF application session context.

NOTE: It may happen that one or more PCC rules (i.e. Service Data Flows) are deactivated at the SMF at certain time, either permanently or temporarily, due to e.g. release of resources or out of credit condition.

The AF shall use the "EventsSubscReqData" data type as described in subclause 4.2.2.2 and shall include in the HTTP POST request message an event within the "evSubsc" attribute with the "event" attribute set to "FAILED_RESOURCES_ALLOCATION".

The PCF shall reply to the AF as described in subclause 4.2.2.2.

As result of this action, the PCF shall set the appropriate subscription to service data flow deactivation for the corresponding PCC rule(s) as described in in 3GPP TS 29.512 [8].

4.2.2.8 Initial provisioning of traffic routing information

This procedure is used by an AF to:

- influence SMF traffic routing decisions to a local access to a Data Network identified by a DNAI; and/or
- request subscriptions to notifications about UP path management events related to the PDU session,

when "Influence on Traffic Routing" feature is supported.

NOTE 1: The AF uses the Npcf_PolicyAuthorization service for requests targeting specific on-going PDU sessions of individual UE(s). The AF requests that target existing or future PDU Sessions of multiple UE(s) or any UE are sent via the NEF and may target multiple PCF(s), as described in 3GPP TS 29.513[7].

The AF shall include in the HTTP POST request message described in subclause 4.2.2.2 the "afRoutReq" attribute of "AfRoutingRequirement" data type with specific routing requirements for the application traffic flows either within "AppSessionContextReq" data type or within the "medComponents" attribute. When provided at both levels, the "afRoutReq" attribute value in the "medComponents" attribute shall have precedence over the "medComponents" flows or for the service indicated in the "afAppId" attribute.

The AF may include traffic routing requirements together with service information.

The AF may include in the "afRoutReq" attribute:

- a) A list of routes to locations of applications in the "routeToLocs" attribute. Each element of the list shall contain:

- a DNAI in the "dnai" attribute to indicate the location of the application towards which the traffic routing is applied; and
 - either a routing profile identifier in the "routeProfId" attribute, or the explicit routing information in the "routeInfo" attribute.
- b) Indication of application relocation possibility in the "appReloc" attribute.
- c) Temporal validity during which the AF request is valid shall be indicated with the "startTime" and "stopTime" attributes.
- d) Spatial validity during which the AF request is valid shall be indicated in terms of validity areas encoded in the "spVal" attribute of "SpatialValidity" data type. The "SpatialValidity" data type consists of either a list of presence reporting area identifiers included in the "praIds" attribute, or a list of presence reporting areas encoded in the attribute "praElements".

The AF may also subscribe to notifications about UP path management events. The AF shall include in the "events" attribute an entry of the "AfEventSubscription" data type to subscribe to:

- notifications of early and/or late DNAI change, using the "DNAI_CHG" value of data type "AfEvent", and the attribute "dnaiChgType" indicating whether the subscription is for "EARLY", "LATE" or "EARLY_LATE";
- notification of the activation/deactivation of the applicability of traffic routing requirements, using the "ROUT_REQ_STATUS_CHG" value of data type "AfEvent".

NOTE 2: The activation/deactivation of the applicability of traffic routing requirements is determined by the temporal validity and validity areas included in the "AfRoutingRequirement" data type.

When the AF requested specific routing to the application traffic or subscribed to notifications of UP path management, and the UE is roaming in a VPLMN, if the AF is located in the HPLMN, for home routed roaming case, the H-PCF shall set to "UNAUTH_TRAFFIC_ROUTING_REQ" the "servAuthInfo" attribute in the HTTP response message to the AF to indicate that the traffic routing request is not authorized.

NOTE 3: After the PCF indicates to the AF that the traffic routing request is not authorized, the AF can e.g. subscribe with the PCF to PLMN change events or request to PCF the termination of the AF session. The AF behaviour after receiving the traffic routing request is not authorized is out of scope of this specification.

The PCF shall reply to the AF as described in subclause 4.2.2.2.

The PCF shall store the routing requirements included in the "afRoutReq" attribute.

The PCF shall check whether the received routing requirements requires PCC rules to be created or provisioned to include or modify traffic steering policies, the AF transaction identifier and the application relocation possibility as specified in 3GPP TS 29.513 [7]. Provisioning of PCC rules to the SMF shall be carried out as specified in 3GPP TS 29.512 [8].

4.2.2.9 Request of access network information

This procedure is used by an AF to request the PCF to report the access network information (i.e. user location and/or user timezone information) at the creation of the "Individual Application Session Context" resource, when the "NetLoc" feature is supported.

The AF shall include in the HTTP POST request message described in subclause 4.2.2.2 the "evSubsc" attribute and shall contain:

- the "events" attribute with an entry of "AfEventSubscription" data type. The AF shall set:
 - a) the "event" attribute to "ANI_REPORT" value; and
 - b) the "notifMethod" attribute to "ONE_TIME" value; and
- the "reqAni" attribute, with the required access network information, i.e. user location and/or user time zone information).

When the PCF determines that the access network does not support the access network information reporting because the SMF does not support the NetLoc feature, the PCF shall respond to the AF including in the "EventsNotification" data type the "netLocAccSupp" attribute set to false (NetLoc access not supported).

The PCF shall reply to the AF as described in subclause 4.2.2.2.

When the PCF determines that the access network supports the access network information reporting, the PCF shall immediately configure the SMF to provide such access information, as specified in 3GPP TS 29.512 [8].

4.2.3 Npcf_PolicyAuthorization_Update service operation

4.2.3.1 General

The Npcf_PolicyAuthorization_Update service operation provides updated application level information from the NF service consumer and optionally communicates with the Npcf_SMPolicyControl service to determine and install the policy according to the information provided by the NF service consumer.

The Npcf_PolicyAuthorization_Update service operation updates an application session context in the PCF.

The following procedures using the Npcf_PolicyAuthorization_Update service operation are supported:

- Modification of service information.
- Gate control.
- Background Data Transfer policy indication at policy authorization update.
- Modification of sponsored connectivity information.
- Modification of Subscription to Service Data Flow QoS notification control.
- Modification of Subscription to Service Data Flow Deactivation.
- Update of traffic routing information.
- Request of access network information.

4.2.3.2 Modification of service information

This procedure is used to modify an existing application session context as defined in 3GPP TS 23.501 [2], 3GPP TS 23.502 [3] and 3GPP TS 23.503 [4].

Figure 4.2.3.2-1 illustrates the modification of service information using HTTP PATCH method.




Figure 4.2.3.2-1: Modification of service information using HTTP PATCH

The AF may modify the application session context information at any time (e.g. due to an AF session modification or internal AF trigger) and invoke the Npcf_PolicyAuthorization_Update service operation by sending the HTTP PATCH

request message to the resource URI representing the "Individual Application Session Context" resource, as shown in figure 4.2.3.2-1, step 1, with the modifications to apply.

The JSON body within the PATCH request shall include the "AppSessionContextUpdateData" data type and shall be encoded according to "JSON Merge Patch", as defined in IETF RFC 7386 [21].

The AF may include the updated service information in the "medComponents" attribute.

The AF may include in the "AppSessionContextUpdateData" data type an AF application identifier in the "afAppId" attribute to trigger the PCF to indicate to the SMF/UPF to perform the application detection based on the operator's policy as defined in 3GPP TS 29.512 [8].

The AF may also create, modify or remove events subscription information by sending the HTTP PATCH request message to the resource URI representing the "Individual Application Session Context" resource.

The AF shall create event subscription information by including in the "AppSessionContextUpdateData" data type the "evSubsc" attribute of "EventSubscReqData" data type with the corresponding list of events to subscribe to; and the "notifUri" attribute with the notification URI where the PCF shall send the notifications.

The AF shall update existing event subscription information by including in the "AppSessionContextUpdateData" data type and updated value of the "evSubsc" attribute of the "EventSubscReqData" data type.

The AF shall remove existing event subscription information by setting to null the "evSubsc" attribute included in the "AppSessionContextUpdateData" data type.

If the PCF cannot successfully fulfil the received HTTP PATCH request due to the internal PCF error or due to the error in the HTTP PATCH request, the PCF shall send the HTTP error response as specified in subclause 5.7.

Otherwise, the PCF shall process the received service information according the operator policy and may decide whether the HTTP request message is accepted or not.

If the "Events Subscription" sub-resource is not found when the AF requests an update of the existing subscription information, the PCF shall respond the AF with an HTTP "404 Not Found" response message with the "cause" attribute set to "SUBSCRIPTION_NOT_FOUND".

If the updated service information is not acceptable (e.g. the subscribed guaranteed bandwidth for a particular user is exceeded), the PCF shall include in an HTTP "403 Forbidden" response message the "cause" attribute set to "REQUESTED_SERVICE_NOT_AUTHORIZED". If the service information provided in the HTTP PATCH request is rejected due to a temporary condition in the network (e.g. the user plane in the cell the user is located is congested), the PCF may include in the "403 Forbidden" response the "cause" attribute set to "REQUESTED_SERVICE_TEMPORARILY_NOT_AUTHORIZED".

If the request is accepted, the PCF shall update the service information with the new information received. Due to the updated service information, the PCF may need to create, modify or delete the related PCC rules as specified in 3GPP TS 29.513 [7] and provide the updated information towards the SMF following the corresponding procedures specified in 3GPP TS 29.512 [8].

Based on the received subscription information from the AF, the PCF may create a subscription to event notifications or may modify the existing subscription to event notifications, for a related PDU session from the SMF, as described in 3GPP TS 29.512 [8] and in 3GPP TS 29.508 [13].

The PCF shall reply with the HTTP response message to the AF and may include the "AppSessionContext" data type payload body with the representation of the modified "Individual Application Session Context" resource and may include the "Events Subscription" sub-resource.

The PCF shall include in the "EvsNotif" attribute:

- if the AF subscribed to the "CHARGING_CORRELATION" event in the HTTP PATCH request, the "event" attribute set to "CHARGING_CORRELATION" and the "anChargIds" attribute containing the access network charging identifier(s) and may include the "anChargAddr" attribute containing the access network charging address;
- if the AF subscribed to the "PLMN_CHG" event in the HTTP PATCH request, the "event" attribute set to "PLMN_CHG" and the "plmnId" attribute including the PLMN identifier if the PCF has previously requested to be updated with this information in the SMF; and

- if the AF subscribed to the "ACCESS_TYPE_CHG" event in the HTTP PATCH request, the "event" attribute set to "ACCESS_TYPE_CHG" and the attributes "accessType" including the access type, "ratType" including the RAT type when applicable for the notified access type, and the "anGwAddr" including access network gateway address when available, if the PCF has previously requested to be updated with this information in the SMF.

The AF subscription to other specific events using the Npcf_PolicyAuthorization_Update request is described in the related subclauses. Notification of events when the applicable information is not available in the PCF when receiving the Npcf_PolicyAuthorization_Update request is described in subclause 4.2.5.

The HTTP response message towards the AF should take place before or in parallel with any required PCC rule provisioning towards the SMF.

If the PCF does not have an existing application session context for the application session context being modified (such as after a PCF failure), the PCF shall reject the HTTP request message with the HTTP response message with the applicable rejection cause.

4.2.3.3 Gate control

This procedure is used by an AF to modify in the PCF the service data flow(s) that are to be enabled or disabled to pass through the PDU session.

The AF shall use the HTTP PATCH method to modify the gate control information.

The AF shall include in the HTTP PATCH request message described in subclause 4.2.3.2 the "fStatus" attribute for the flows to be enabled or disabled with the appropriate value.

As result of this action, the PCF shall set the appropriate gate status for the corresponding active PCC rule(s).

The PCF shall reply to the AF as described in subclause 4.2.3.2.

4.2.3.4 Background Data Transfer policy indication at policy authorization update

This procedure is used by an AF to indicate at policy authorization update a transfer policy negotiated for background data transfer using the Npcf_BDTPolicyControl service as described in 3GPP TS 29.554 [14].

The AF may include in the HTTP PATCH request message described in subclause 4.2.3.2 a new reference id in the "bdtRefId" attribute.

NOTE 1: The PCF will retrieve the corresponding transfer policy from the UDR based on the reference identifier within the "bdtRefId" attribute. In case only one PCF is deployed in the network, transfer policies can be locally stored in the PCF and the interaction with the UDR is not required.

If the PCF cannot retrieve the transfer policy, the PCF shall set to TP_NOT_KNOWN the "servAuthInfo" attribute in the HTTP response message to the AF to indicate that the transfer policy is unknown.

If the time window of the received transfer policy has expired, the PCF shall set to TP_EXPIRED the "servAuthInfo" attribute in the HTTP response message to indicate to the AF that the transfer policy has expired. Otherwise, if the time window of the received transfer policy has not yet occurred, the PCF shall set to TP_NOT_YET_OCCURRED the "servAuthInfo" attribute in the HTTP response message to the AF to indicate that the time window of the transfer policy has not yet occurred.

NOTE 2: In the case that the PCF cannot retrieve the transfer policy, the transfer policy time window has not yet occurred or the transfer policy expired, the PCF makes the decision without considering the transfer policy.

The PCF shall reply to the AF as described in subclause 4.2.3.2.

4.2.3.5 Modification of sponsored connectivity information

This procedure is used by an AF to modify sponsored data connectivity when Sponsored Connectivity feature is supported.

The AF shall use the HTTP PATCH method to modify the sponsored connectivity information.

The AF shall include in the HTTP PATCH request message described in subclause 4.2.3.2 an application service provider identity and a sponsor identity within the "aspId" attribute and "sponId" attribute, and optionally an indication of whether to enable or disable sponsored data connectivity within the "sponStatus" attribute set to the applicable value to provide sponsored connectivity information or to update existing sponsored connectivity information.

If the AF requests to enable sponsored data connectivity the AF shall change the "sponStatus" attribute value to "SPONSOR_ENABLED".

If the AF requests to disable sponsored data connectivity the AF shall provide an indication to disable sponsored data connectivity to the PCF by setting the "sponStatus" attribute to "SPONSOR_DISABLED".

To support the usage monitoring of sponsored data connectivity, the AF may also include in the HTTP PATCH a new or modified "evSubsc" attribute of "EventsSubscReqData" data type with:

- the usage thresholds to apply in the "usgThres" attribute; and
- the subscription to usage monitoring for sponsored data connectivity in an entry of the "events" attribute of the "AfEventSubscription" data type with the "event" attribute set to "USAGE_REPORT".

NOTE 1: If the AF is in the user plane, the AF can handle the usage monitoring and therefore it is not required to provide a usage threshold to the PCF as part of the sponsored data connectivity information.

When the AF indicated to enable sponsored data connectivity, and the UE is roaming with the visited access case, the following procedures apply:

- If the AF is located in the HPLMN, for home routed roaming case and when operator policies do not allow accessing the sponsored data connectivity with this roaming case, the H-PCF shall reject the service request and shall include in the HTTP "403 Forbidden" response message the "cause" attribute set to "UNAUTHORIZED_SPONSORED_DATA_CONNECTIVITY".
- If the AF is located in the VPLMN, the V-PCF shall reject the service request and shall include in the HTTP "403 Forbidden" response message the "cause" attribute set to "UNAUTHORIZED_SPONSORED_DATA_CONNECTIVITY".

When the AF indicated to enable sponsored data connectivity, and the UE is in the non-roaming case or roaming with the home routed case and the operator policies allow accessing the sponsored data connectivity with this roaming case, the following procedures apply:

- If the SMF does not support sponsored connectivity and the required reporting level for that service indicates a sponsored connectivity level according to 3GPP TS 29.512 [8], then the PCF shall reject the request and shall include in the HTTP "403 Forbidden" response message the "cause" attribute set to "REQUESTED_SERVICE_NOT_AUTHORIZED".
- If the SMF supports sponsored data connectivity feature or the required reporting level is different from sponsored connectivity level as described in 3GPP TS 29.512 [8], then the PCF, based on operator policies, shall check whether it is required to validate the sponsored connectivity data. If it is required, it shall perform the authorizations based on sponsored data connectivity profiles. If the authorization fails, the PCF shall include in the HTTP "403 Forbidden" response message the "cause" attribute set to "UNAUTHORIZED_SPONSORED_DATA_CONNECTIVITY".

NOTE 2: The PCF is not required to verify that a trust relationship exists between the operator and the sponsors.

The PCF shall reply to the AF as described in subclause 4.2.3.2.

4.2.3.6 Modification of Subscription to Service Data Flow QoS notification control

This procedure is used in the AF to modify in the PCF the subscription to notification about the GBR QoS targets cannot be fulfilled.

The AF shall use the HTTP PATCH method to update the "Events Subscription" sub-resource together with the modifications to the "Individual Application Session" sub-resource.

The AF shall include in the HTTP PATCH request message described in subclause 4.2.3.2 the updated values of the "EventsSubscReqData" data type, which either include in the "events" attribute a new element with the "event" attribute

set to "QOS_NOTIF_CONTROL" or remove in the "events" attribute an existing element with the "event" attribute set to "QOS_NOTIF_CONTROL".

As result of this action, the PCF shall set the appropriate subscription to QoS notification control for the corresponding active PCC rule(s) as described in 3GPP TS 29.512 [8].

The PCF shall reply to the AF as described in subclause 4.2.3.2.

4.2.3.7 Modification of Subscription to Service Data Flow Deactivation

This procedure is used by an AF to modify in the PCF the subscription to the notification of deactivation of one or more Service Data Flows within the AF application session context.

The AF shall use the HTTP PATCH method to update the "Events Subscription" sub-resource together with the modifications to the "Individual Application Session" sub-resource.

The AF shall include in the HTTP PATCH request message described in subclause 4.2.3.2 the updated values of the "EventsSubscReqData" data type, which either include in the "events" attribute a new element with the "event" attribute set to "FAILED_RESOURCES_ALLOCATION" or remove in the "events" attribute an existing element with the "event" attribute set to "FAILED_RESOURCES_ALLOCATION".

The PCF shall reply to the AF as described in subclause 4.2.3.2.

As result of this action, the PCF shall set the appropriate subscription to service data flow deactivation for the corresponding PCC rule(s) as described in in 3GPP TS 29.512 [8].

4.2.3.8 Update of traffic routing information

This procedure is used by an AF to modify in the PCF the traffic routing information to a local access to a DNN, and/or to modify the subscription to notifications about UP path management when "Influence on Traffic Routing" feature is supported.

The AF shall use the HTTP PATCH method.

To modify traffic routing information, the AF shall include in the HTTP PATCH request message described in subclause 4.2.3.2 an updated "afRoutReq" attribute(s) with the modified traffic routing information.

To modify the subscription to notifications about UP path management events, the AF shall include in the HTTP PATCH request message described in subclause 4.2.3.2 the updated values of the "evSubsc" attribute with the modified subscription to UP path management events.

When the AF requested specific routing to the application traffic or subscribed to notifications of UP path management, and the UE is roaming in a VPLMN, if the AF is located in the HPLMN, for home routed roaming case, the H-PCF shall set to "UNAUTH_TRAFFIC_ROUTING_REQ" the "servAuthInfo" attribute in the HTTP response message to the AF to indicate that the traffic routing request is not authorized.

NOTE: After the PCF indicates to the AF that the traffic routing request is not authorized, the AF can e.g. subscribe with the PCF to PLMN change events or request to PCF the termination of the AF session. The AF behaviour after receiving the traffic routing request is not authorized is out of scope of this specification.

The PCF shall reply to the AF as described in subclause 4.2.3.2.

The PCF shall store the application routing requirements included in the "afRoutReq" attribute.

The PCF shall check whether the updated application routing requirements require PCC rules to be created or modified to include updated traffic steering policies, or the AF transaction identifier, or to update the application relocation possibility as specified in 3GPP TS 29.513 [7]. Provisioning of PCC rules to the SMF shall be carried out as specified at 3GPP TS 29.512 [8].

4.2.3.9 Request of access network information

This procedure is used by an AF to request access network information for an existing "Individual Application Session Context" resource at service information modification when the "NetLoc" feature is supported. Subclause 4.2.6.5

describes the AF request of access network information without providing service information when the "NetLoc" feature is supported.

The AF shall include in the HTTP PATCH method described in subclause 4.2.3.2 the "evSubsc" attribute and shall contain:

- the "events" attribute with an entry of "AfEventSubscription" data type. The AF shall set:
 - a) the "event" attribute to "ANI_REPORT" value; and
 - b) the "notifMethod" attribute to "ONE_TIME" value; and
- the "reqAni" attribute, with the required access network information, i.e. user location and/or user time zone information).

When the PCF determines that the access network does not support the access network information reporting because the SMF does not support the NetLoc feature, the PCF shall respond to the AF including in the "EventsNotification" data type the "netLocAccSupp" attribute set to false (NetLoc access not supported).

The PCF shall reply to the AF as described in subclause 4.2.3.2.

When the PCF determines that the access network supports the access network information reporting, the PCF shall immediately configure the SMF to provide such access information, as specified in 3GPP TS 29.512 [8].

4.2.4 Npcf_PolicyAuthorization_Delete service operation

4.2.4.1 General

The Npcf_PolicyAuthorization_Delete service operation provides means for the NF service consumer to delete the context of application session information.

The following procedures using the Npcf_PolicyAuthorization_Delete service operation are supported:

- AF application session context termination.
- Reporting usage for sponsored data connectivity.
- Request and report of access network information.

4.2.4.2 AF application session context termination

This procedure is used to terminate an AF application session context for the service as defined in 3GPP TS 23.501 [2], 3GPP TS 23.502 [3] and 3GPP TS 23.503 [4].

Figure 4.2.4.2-1 illustrates the application session context termination.




Figure 4.2.4.2-1: Application session context termination

When an AF session is terminated, and if the AF application session context was created as described in subclause 4.2.2, the AF shall invoke the Npcf_PolicyAuthorization_Delete service operation to the PCF using an HTTP POST request, as shown in figure 4.2.4.2-1, step 1.

The AF shall set the request URI to "{apiRoot}/npcf-policyauthorization/v1/app-sessions/{appSessionId}/delete".

The AF may include in the body of the HTTP POST the "EventSubscReqData" data type with the "evSubsc" attribute indicating the corresponding list of events to subscribe to.

When the PCF receives the HTTP POST request from the AF, indicating the termination of the AF application session context information, the PCF shall acknowledge that request by sending an HTTP response message with the corresponding status code.

If the HTTP POST request from the AF is accepted, the PCF shall send to the AF a "200 OK" response to HTTP POST request, as shown in figure 4.2.4.2-1, step 2, including in the "EventsNotification" data type the "evNotif" attribute indicating the event to report to the AF, as described in subclause 4.2.5.2. Otherwise the PCF shall send to the AF a "204 No Content". Afterwards, the PCF shall free the network resources allocated for the Service Data Flow(s) corresponding to the deleted AF application session context information. In order to do that, the PCF shall initiate the request for the removal of any related PCC rules from the SMF following the corresponding procedures specified in 3GPP TS 29.512 [8] and 3GPP TS 29.508 [13].

If the HTTP POST request from the AF is rejected, the PCF shall indicate in the response to HTTP POST request the cause for the rejection as specified in subclause 5.7.

4.2.4.3 Reporting usage for sponsored data connectivity

When Sponsored Connectivity is supported, and the AF indicated to enable sponsored data connectivity and the AF provided usage thresholds for such sponsor to the PCF, the PCF shall report accumulated usage to the AF using the response of the Npcf_PolicyAuthorization_Delete service operation.

This procedure is initiated when:

- the "Individual Application Session Context" is deleted by the AF; or
- the PCF requests the deletion of the "Individual Application Session Context" to the AF, as described in subclause 4.2.5.3, due to PDU session termination, the termination of all the service data flows of the AF session or the home operator policy disallowing the UE accessing the sponsored data connectivity in the roaming case.

The PCF shall notify the AF by including the "EventsNotification" data type in the response of the HTTP POST request as described in subclause 4.2.4.2.

The PCF shall include:

- an event of the "AfEventNotification" data type in the "evNotif" attribute with the matched event "USAGE_REPORT" in the "event" attribute; and
- the usage encoded in the "usgRep" attribute.

4.2.4.4 Request and report of access network information

This procedure is used by an AF to request the PCF to report the access network information (i.e. user location and/or user timezone information) at the deletion of the "Individual Application Session Context" resource when the "NetLoc" feature is supported.

This procedure is initiated when:

- the "Individual Application Session Context" is deleted by the AF; or
- the PCF requests the deletion of the "Individual Application Session Context" to the AF due to PDU session termination, or the termination of all the service data flows of the AF session, as described in subclause 4.2.5.3.

The AF shall include in the HTTP POST request message described in subclause 4.2.4.2 the "evSubsc" attribute, that shall contain:

- the "events" attribute with an entry of "AfEventSubscription" data type that shall include:

- a) the "event" attribute set to "ANI_REPORT"; and
- b) the "notifMethod" attribute set to "ONE_TIME"; and
- the "reqAni" attribute, with the required access network information, i.e. user location and/or user time zone information).

When the PCF determines that the access network does not support the access network information reporting because the SMF does not support the NetLoc feature, the PCF shall respond to the AF including in the "EventsNotification" data type the "netLocAccSupp" attribute set to false (NetLoc access not supported).

When the PCF determines that the access network supports the access network information reporting, the PCF shall immediately configure the SMF to provide such access information, as specified in 3GPP TS 29.512 [8]. When the PCF receives the access network information from the SMF, the PCF shall provide the corresponding access network information in the "200 OK" response to the AF including in the "EventsNotification" data type:

- the user location information in the "ueLoc" attribute, if available and required;
- the time user location information was last known in the "ueLocTime" attribute, if available and required;
- the serving PLMN network code and country code in the "plmnCcNc", if user location information is required but not available; and/or
- the UE timezone in the "ueTimeZone" attribute if required.

In case of untrusted non-3GPP WLAN access, the PCF shall provide the following WLAN access network information:

- if user location is required, the user location in a WLAN network in the "n3gaLocation" attribute included in the "ueLoc" attribute, that shall contain:
 - a) the user local IP address in the "ueLocalIpv4" or "ueLocalIpv6" attribute, if available;
 - b) the UDP source port in the "udpPort" if available;
 - c) the TCP source port in the "tcpPort" if available;
- the time the user location information was last known in the "ueLocTime" attribute, if available and required; and
- the UE time zone in the "ueTimeZone" attribute if required.

The PCF shall also provide the "evNotif" attribute with an entry of "AfEventNotification" data type that shall include the "event" attribute set to "ANI_REPORT".

4.2.5 Npcf_PolicyAuthorization_Notify service operation

4.2.5.1 General

The Npcf_PolicyAuthorization_Notify service operation enables notification to NF service consumers that the previously subscribed event for the existing application session context occurred or that the application session context is no longer valid.

The following procedures using the Npcf_PolicyAuthorization_Notify service operation are supported:

- Notification about application session context event.
- Notification about application session context termination.
- Notification about Service Data Flow QoS notification control.
- Notification about service data flow deactivation.
- Reporting usage for sponsored data connectivity.
- Reporting access network information.

4.2.5.2 Notification about application session context event

This procedure is invoked by the PCF to notify the AF when a certain, previously subscribed, application session context event occurs, as defined in 3GPP TS 23.501 [2], 3GPP TS 23.502 [3] and 3GPP TS 23.503 [4].

Figure 4.2.5.2-1 illustrates the notification about application session context event.




Figure 4.2.5.2-1: Notification about application session context event

When the PCF determines that the event for the existing AF application session context, to which the AF has subscribed to, occurred e.g. upon reception of an event notification for a PDU session from the SMF as described in 3GPP TS 29.512 [8], the PCF shall invoke the `Npcf_PolicyAuthorization_Notify` service operation by sending the HTTP POST request (as shown in figure 4.2.5.2-1, step 1) to the AF using the notification URI received in the subscription creation (or modification), as specified in subclause 4.2.6, and appending the "notify" segment path at the end of the URI. The PCF shall provide in the body of the HTTP POST request the "EventsNotification" data type including:

- the Events Subscription resource identifier in the "evSubsUri" attribute; and
- the list of the reported events in the "evNotif" attribute. For each reported event, the "AfEventNotification" data type shall include the event identifier and may include additional event information.

The PCF shall include in the "EvsNotif" attribute:

- if the AF subscribed to the "CHARGING_CORRELATION" event, the "event" attribute set to "CHARGING_CORRELATION" and the "anChargIds" attribute containing the access network charging identifier(s) and may include the "anChargAddr" attribute containing the access network charging address;
- if the AF subscribed to the "PLMN_CHG" event, the "event" attribute set to "PLMN_CHG" and the "plmnId" attribute including the PLMN identifier if the PCF has requested to be updated with this information in the SMF; and
- if the AF subscribed to the "ACCESS_TYPE_CHG" event, the "event" attribute set to "ACCESS_TYPE_CHG" and the attributes "accessType" including the access type, "ratType" including the RAT type when applicable for the notified access type, and the "anGwAddr" including access network gateway address when available.

The AF notification of other specific events using the `Npcf_PolicyAuthorization_Notify` request is described in the related subclauses.

Upon the reception of the HTTP POST request from the PCF indicating that the PDU session and/or service related event occurred, the AF shall acknowledge that request by sending an HTTP response message with the corresponding status code.

If the HTTP POST request from the PCF is accepted, the AF shall acknowledge the receipt of the event notification with a "204 No Content" response to HTTP POST request, as shown in figure 4.2.5.2-1, step 2.

If the HTTP POST request from the PCF is not accepted, the AF shall indicate in the response to HTTP POST request the cause for the rejection as specified in subclause 5.7.

4.2.5.3 Notification about application session context termination

This procedure is invoked by the PCF to notify the AF that the application session context is no longer valid, as defined in 3GPP TS 23.501 [2], 3GPP TS 23.502 [3] and 3GPP TS 23.503 [4].

Figure 4.2.5.3-1 illustrates the notification about application session context termination.




Figure 4.2.5.3-1: Notification about application session context termination

When the PCF determines that the AF application session context is no longer valid, the PCF shall invoke the `Npcf_PolicyAuthorization_Notify` service operation by sending the HTTP POST request (as shown in figure 4.2.5.3-1, step 1) using the notification URI received in the "Individual Application Session Context" context creation, as specified in subclause 4.2.2, and appending the "termination" segment path at the end of the URI, to trigger the AF to request the application session context termination (see subclause 4.2.4.2). The PCF shall provide in the body of the HTTP POST request the "TerminationInfo" data type including:

- the application session context identifier in the "resUri" attribute; and
- the application session context termination cause in the "termCause" attribute of the "TerminationCause" data type, indicating either "PDU_SESSION_TERMINATION" or "ALL_SDF_DEACTIVATION".

Upon the reception of the HTTP POST request from the PCF requesting the application session context termination, the AF shall acknowledge that request by sending an HTTP response message with the corresponding status code.

If the HTTP POST request from the PCF is accepted, the AF shall acknowledge the receipt of the application session context termination request with a "204 No Content" response to HTTP POST request (as shown in figure 4.2.5.3-1, step 2) and shall invoke the `Npcf_PolicyAuthorization_Delete` service operation to the PCF as described in subclause 4.2.4.

If the HTTP POST request from the PCF is not accepted, the AF shall indicate in the response to HTTP POST request the cause for the rejection as specified in subclause 5.7.

4.2.5.4 Notification about Service Data Flow QoS notification control

When the PCF gets the knowledge that one or more SDFs:

- cannot fulfil the GBR QoS targets; or
- can fulfil again the GBR QoS targets;

the PCF shall inform the AF accordingly if the AF has previously subscribed as described in subclauses 4.2.2.6 and 4.2.3.6.

The PCF shall notify the AF by including the "EventsNotification" data type in the body of the HTTP POST request as described in subclause 4.2.5.2.

The PCF shall include within the "evNotif" attribute an event of the "AfEventNotification" data type with:

- the matched event "QOS_NOTIF_CONTROL" in the "event" attribute;

- the affected service flows encoded in the "flows" attribute; and
- the "notifType" attribute to indicate whether the GBR targets for the SDFs are "NOT_FULFILLED" or "FULFILLED".

When the AF receives the HTTP POST request, it shall acknowledge the request by sending a "204 No Content" response to the PCF. The AF may also update the AF application session context information by sending an HTTP PATCH request to the PCF.

Signalling flows for Service Data Flow QoS notification control are presented in 3GPP TS 29.513 [7].

4.2.5.5 Notification about Service Data Flow Deactivation

When the PCF gets the knowledge that one or more SDFs have been deactivated, the PCF shall inform the AF accordingly if the AF has previously subscribed as described in subclauses 4.2.2.7 and 4.2.3.7.

When not all the service data flows within the AF application session context are affected, the PCF shall notify the AF by including the "EventsNotification" data type in the body of the HTTP POST request as described in subclause 4.2.5.2.

The PCF shall include within the "evNotif" attribute an event of "AfEventNotification" data type indicating the matched event "FAILED_RESOURCES_ALLOCATION" in the "event" attribute and the deactivated IP flows encoded in the "flows" attribute.

When the AF receives the HTTP POST request, it shall acknowledge the request by sending a "204 No Content" response to the PCF. The AF may also update the AF application session context information by sending an HTTP PATCH request to the PCF.

When all the service data flows within the AF session are affected, the PCF shall inform the AF by sending a notification about application session context termination as defined in subclause 4.2.2.2.

Signalling flows for Service Data Flow Deactivation cases are presented in 3GPP TS 29.513 [7].

4.2.5.6 Reporting usage for sponsored data connectivity

When Sponsored Connectivity is supported, the AF enabled sponsored data connectivity and the AF provided usage thresholds for such sponsor to the PCF, the PCF shall report accumulated usage to the AF using the Npcf_PolicyAuthorization_Notify service operation when:

- the PCF detects that the usage threshold provided by the AF has been reached; or
- the AF disables the sponsored data connectivity.

The PCF shall notify the AF of the accumulated usage by including the "EventsNotification" data type in the body of the HTTP POST request as described in subclause 4.2.5.2.

The PCF shall include:

- an event of the "AfEventNotification" data type in the "evNotif" attribute with the matched event "USAGE_REPORT" in the "event" attribute; and
- the accumulated usage, corresponding to the usage since the last report to the AF, encoded in the "usgRep" attribute.

When the AF receives the HTTP POST request, it shall acknowledge the request by sending a "204 No Content" response to the PCF. The AF may terminate the AF session sending an HTTP POST as described in subclause 4.2.4.2 or update the AF application session context information by providing a new usage threshold sending an HTTP PATCH request to the PCF as described in subclause 4.2.3.5 or an HTTP PUT request to the PCF as described in subclause 4.2.6.4.

NOTE: After the PCF reports the accumulated usage to the AF, the AF can provide a new usage threshold to the PCF. The monitoring will not start until the PCF receives the new threshold from the AF and provides it to the SMF.

4.2.5.7 Reporting access network information

This procedure is used by the PCF to report the access network information (i.e. user location and/or user timezone information) to the AF when the "NetLoc" feature is supported.

When the PCF receives the access network information from the SMF, the PCF shall include the "EventsNotification" data type in the body of the HTTP POST request sent to the AF as described in subclause 4.2.5.2.

The PCF shall include in the "EventsNotification" data type:

- the user location information in the "ueLoc" attribute, if available;
- the time user location information was last known in the "ueLocTime" attribute, if available;
- the serving PLMN network code and country code in the "plmnCcNc", if user location information is not available; and/or
- the UE timezone in the "ueTimeZone" attribute.

When the access network is an untrusted non-3GPP WLAN access, the PCF shall provide the following WLAN access network information instead:

- if user location is required, the user location in a WLAN network in the "n3gaLocation" attribute included in the "ueLoc" attribute, that shall contain:
 - a) the user local IP address in the "ueLocalIpv4" or "ueLocalIpv6" attribute, if available;
 - b) the UDP source port in the "udpPort" if available;
 - c) the TCP source port in the "tcpPort" if available;
- the time the user location information was last known in the "ueLocTime" attribute, if available and required; and
- the UE time zone in the "ueTimeZone" attribute if required.

The PCF shall also provide the "evNotifs" attribute with an entry of "AfEventNotification" data type with the "event" attribute set to "ANI_REPORT".

NOTE 1: The PCF receives the access network information from the SMF if it is requested by the AF previously or all the SDFs of an AF session or the PDU session is terminated.

When the PCF receives from the SMF that the access network does not support reporting of access network information the PCF shall include the "EventsNotification" data type in the body of the HTTP POST request sent to the AF with:

- the "netLocAccSupp" attribute set to false (NetLoc access not supported); and
- the "evNotifs" attribute with an entry of "AfEventNotification" data type with the "event" attribute set to "ANI_REPORT".

NOTE 2: The 3GPP EPS, 3GPP 5GS, and Untrusted WLAN support access network information reporting in this Release.

The PCF shall not send an Npcf_PolicyAuthorization_Notify with the "event" attribute set to "ANI_REPORT" value to report any subsequently received access network information to the AF, unless the AF sends a new request for access network information.

4.2.6 Npcf_PolicyAuthorization_Subscribe service operation

4.2.6.1 General

The Npcf_PolicyAuthorization_Subscribe service operation enables NF service consumers handling of subscription to events for the existing application session context. Subscription to events shall be created:

- within the application session context establishment procedure by invoking the Npcf_PolicyAuthorization_Create service operation, as described in subclause 4.2.2; or
- within the application session context modification procedure by invoking the Npcf_PolicyAuthorization_Update service operation, as described in subclause 4.2.3; or
- by invoking the Npcf_PolicyAuthorization_Subscribe service operation for the existing application session context, as described in subclause 4.2.6.2.

The following procedure using the Npcf_PolicyAuthorization_Subscribe service operation is supported:

- Handling of subscription to events for the existing application session context.
- Initial subscription to events without provisioning of service information.
- Subscription to usage monitoring of sponsored data connectivity.
- Request of access network information.

4.2.6.2 Handling of subscription to events for the existing application session context

This procedure is used to create a subscription to events for the existing AF application session context bound to the corresponding PDU session or to modify an existing subscription, as defined in 3GPP TS 23.501 [2], 3GPP TS 23.502 [3] and 3GPP TS 23.503 [4].

Figure 4.2.6.2-1 illustrates the creation of events subscription information using HTTP PUT method.




Figure 4.2.6.2-1: Creation or modification of events subscription information using HTTP PUT

Figure 4.2.6.2-2 illustrates the modification of events subscription information using HTTP PUT method.




Figure 4.2.6.2-2: Modification of events subscription information using HTTP PUT

When the AF decides to create a subscription to one or more events for the existing application session context or to modify an existing subscription previously created by itself at the PCF, the AF shall invoke the Npcf_PolicyAuthorization_Subscribe service operation by sending the HTTP PUT request to the resource URI representing the "Events Subscription" sub-resource in the PCF, as shown in figure 4.2.6.2-1, step 1 and figure 4.2.6.2-2, step 1. The AF shall provide in the "EventsSubscReqData" data type of the body of the HTTP PUT request:

- the "evSubsc" attribute with the list of events to be subscribed; and
- the "notifUri" attribute that includes the Notification URI to indicate to the PCF where to send the notification of the subscribed events if not provided before.

Upon the reception of the HTTP PUT request from the AF, the PCF shall decide whether the received HTTP PUT request is accepted.

If the HTTP PUT request from the AF is rejected, the PCF shall indicate in the HTTP response the cause for the rejection as specified in subclause 5.7.

If the "Events Subscription" sub-resource is not found when the AF requests an update of the existing subscription information, the PCF shall respond the AF with an HTTP "404 Not Found" response message with the "cause" attribute set to "SUBSCRIPTION_NOT_FOUND".

If the PCF accepted the HTTP PUT request to create a subscription to events, the PCF shall create the "Events Subscription" sub-resource and shall send the HTTP response message to the AF as shown in figure 4.2.6.2-1, step 2. The PCF shall include in the "201 Created" response:

- a Location header field that shall contain the URI of the created "Events Subscription" sub-resource i.e. "{apiRoot}/npcf-policyauthorization/v1/app-sessions/{appSessionId}/events-subscription"; and
- an "EventsSubscReqData" data type and may include the "EventsNotification" data type in the payload body containing the representation of the created "Events Subscription" sub-resource.

The PCF shall include in the "EvsNotif" attribute:

- if the AF subscribed to the "CHARGING_CORRELATION" event in the HTTP PUT request, the "event" attribute set to "CHARGING_CORRELATION" and the "anChargIds" attribute containing the access network charging identifier(s) and may include the "anChargAddr" attribute containing the access network charging address;
- if the AF subscribed to the "PLMN_CHG" event in the HTTP PUT request, the "event" attribute set to "PLMN_CHG" and the "plmnId" attribute including the PLMN identifier if the PCF has previously requested to be updated with this information in the SMF; and
- if the AF subscribed to the "ACCESS_TYPE_CHG" event in the HTTP PUT request, the "event" attribute set to "ACCESS_TYPE_CHG" and the attributes "accessType" including the access type, "ratType" including the RAT type when applicable for the notified access type, and the "anGwAddr" including access network gateway address when available, if the PCF has previously requested to be updated with this information in the SMF.

If the PCF accepted the HTTP PUT request to modify the events subscription, the PCF shall modify the "Events Subscription" sub-resource and shall send the HTTP "204 No Content" response to the AF as shown in figure 4.2.6.2-2, step 2. Based on the received subscription information from the AF, the PCF may create a subscription to event notifications or may modify the existing subscription to event notifications, for a related PDU session from the SMF, as described in 3GPP TS 29.512 [8] and 3GPP TS 29.508 [13].

4.2.6.3 Initial subscription to events without provisioning of service information

The AF may subscribe with the PCF to events notification without providing service information. Figure 4.2.6.3-1 illustrates the initial subscription to events without provisioning of service information.




Figure 4.2.6.3-1: Initial Subscription to events without provisioning of service information

When an AF establishes an application session context with the PCF to subscribe to events and does not require PCC control for the related media, the AF shall invoke the `Npcf_PolicyAuthorization_Subscribe` service operation by sending the HTTP POST request to the resource URI representing the "Application Sessions" collection resource of the PCF, as shown in figure 4.2.6.3-1, step 1.

The AF shall include in the "AppSessionContext" data type in the payload body of the HTTP POST request:

- either the "ueMac" attribute containing the UE MAC address, or the "ueIpv4" attribute or "ueIpv6" attribute containing the UE IPv4 or the IPv6 address; and
- the "evSubsc" attribute of "EventSubscReqData" data type to request the notification of certain user plane events. The AF shall include the events to subscribe to in the "eventSubsc" attribute, and the notification URI where to address the `Npcf_PolicyAuthorization_Notify` service operation in the "notifUri" attribute.

The AF may provide in the "AppSessionContext" data type the DNN in the "dnn" attribute, SUPI in the "supi" attribute or other information if available.

If the PCF cannot successfully fulfil the received HTTP POST request due to the internal PCF error or due to the error in the HTTP POST request, the PCF shall send the HTTP error response as specified in subclause 5.7.

Otherwise, the information required for session binding (UE IPv4 or IPv6 address, DNN, SUPI and other available information) is provisioned in the "Individual Application Session Context" resource. The events subscription is provisioned in the "Events Subscription" sub-resource.

Based on the received subscription information from the AF, the PCF may create a subscription to event notifications for a related PDU session from the SMF, as described in 3GPP TS 29.512 [8].

If the PCF created the "Events Subscription" sub-resource within the "Individual Application Session Context" resource, the PCF shall send to the AF a "201 Created" response to the HTTP POST request, as shown in figure 4.2.6.3-1, step 2. The PCF shall include in the "201 Created" response:

- a Location header field; and
- an "AppSessionContext" data type in the payload body.

The Location header field shall contain the URI of the created events subscription sub-resource i.e. "`{apiRoot}/npcf-policyauthorization/v1/app-sessions/{appSessionId}/events-subscription`".

The "AppSessionContext" data type payload body shall contain the representation of the created "Individual Application Session Context" resource and "Events Subscription" sub-resource.

The PCF shall include in the "EvsNotif" attribute:

- if the AF subscribed to the event "CHARGING_CORRELATION" in the HTTP POST request, the "event" attribute set to "CHARGING_CORRELATION" and the "anChargId" attribute containing the access network charging identifier(s) and may include the "anChargAddr" attribute containing the access network charging address;

- if the AF subscribed to the event "PLMN_CHG" in the HTTP POST request, the "event" attribute set to "PLMN_CHG" and the "plmnId" attribute including the PLMN identifier if the PCF has previously requested to be updated with this information in the SMF; and
- if the AF subscribed to the event "ACCESS_TYPE_CHG" in the HTTP POST request, the "event" attribute set to "ACCESS_TYPE_CHG" and the attributes "accessType" including the access type, "ratType" including the RAT type when applicable for the notified access type, and the "anGwAddress" including access network gateway address when available, if the PCF has previously requested to be updated with this information in the SMF.

4.2.6.4 Subscription to usage monitoring of sponsored data connectivity

This procedure is used by an AF to subscribe with the PCF to usage monitoring of sponsored data connectivity or to provide updated usage thresholds for the existing application session context, when the "Sponsored Connectivity" feature is supported.

The AF shall include in the HTTP PUT request message described in subclause 4.2.6.2 the "EventSubscReqData" data type, that shall contain:

- the "events" attribute with a new entry of the "AfEventSubscription" data type with the "event" attribute set to "USAGE_REPORT"; and
- the "usgThres" attribute with the usage thresholds to apply.

The PCF shall reply to the AF as described in subclause 4.2.6.2.

4.2.6.5 Request of access network information

This procedure is used by an AF to request the PCF to report the access network information (i.e. user location and/or user timezone information) without providing service information when the "NetLoc" feature is supported.

The AF can request access network information without providing service information:

- at initial subscription to events, using the HTTP POST request message as described in subclause 4.2.6.3; and
- at modification of the subscription to events, using the HTTP PUT request message as described in subclause 4.2.6.2.

The AF shall include in the HTTP request message the "evSubsc" attribute, that shall contain:

- the "events" attribute with an entry of "AfEventSubscription" data type that shall include:
 - a) the "event" attribute set to "ANI_REPORT"; and
 - b) the "notifMethod" attribute set to "ONE_TIME"; and
- the "reqAni" attribute, with the required access network information, i.e. user location and/or user time zone information).

When the PCF determines that the access network does not support the access network information reporting because the SMF does not support the NetLoc feature, the PCF shall respond to the AF including in the "EventsNotification" data type the "netLocAccSupp" attribute set to false (NetLoc access not supported).

The PCF shall reply to the AF with the HTTP POST response as described in subclause 4.2.6.3 and with the HTTP PUT response as described in subclause 4.2.6.2.

When the PCF determines that the access network supports the access network information reporting, the PCF shall immediately configure the SMF to provide such access information, as specified in 3GPP TS 29.512 [8].

4.2.7 Npcf_PolicyAuthorization_Unsubscribe service operation

4.2.7.1 General

The Npcf_PolicyAuthorization_Unsubscribe service operation enables NF service consumers to remove subscription to all subscribed events for the existing application session context. Subscription to events shall be removed:

- by invoking the Npcf_PolicyAuthorization_Unsubscribe service operation for the existing application session context, as described in subclause 4.2.7.2; or
- within the application session context modification procedure by invoking the Npcf_PolicyAuthorization_Update service operation, as described in subclause 4.2.3; or
- within the application session context termination procedure by invoking the Npcf_PolicyAuthorization_Delete service operation, as described in subclause 4.2.4.

The following procedure using the Npcf_PolicyAuthorization_Unsubscribe service operation is supported:

- Unsubscription to events.

4.2.7.2 Unsubscription to events

This procedure is used to unsubscribe to all subscribed events for the existing AF application session context, as defined in 3GPP TS 23.501 [2], 3GPP TS 23.502 [3] and 3GPP TS 23.503 [4].

Figure 4.2.7.2-1 illustrates the unsubscription to events using the HTTP DELETE method.




Figure 4.2.7.2-1: Removal of events subscription information using HTTP DELETE

When the AF decides to unsubscribe to all subscribed events for the existing application session context, the AF shall invoke the Npcf_PolicyAuthorization_Unsubscribe service operation by sending the HTTP DELETE request message to the resource URI representing the "Events Subscription" sub-resource in the PCF, as shown in figure 4.2.7.2-1, step 1.

Upon the reception of the HTTP DELETE request message from the AF, the PCF shall decide whether the received HTTP request message is accepted.

If the HTTP DELETE request message from the AF is accepted, the PCF shall delete "Events Subscription" sub-resource and shall send to the AF a HTTP "204 No Content" response message. The PCF may delete the existing subscription to event notifications for the related PDU session from the SMF as described in 3GPP TS 29.512 [8] and 3GPP TS 29.508 [13].

If the HTTP DELETE request message from the AF is rejected, the PCF shall indicate in the HTTP response message the cause for the rejection as specified in subclause 5.7.

If the "Events Subscription" sub-resource is not found when the AF requests the deletion of the existing subscription information, the PCF shall respond the AF with an HTTP "404 Not Found" response message with the "cause" attribute set to "SUBSCRIPTION_NOT_FOUND".

5 Npcf_PolicyAuthorization Service API

5.1 Introduction

The Npcf_PolicyAuthorization Service shall use the Npcf_PolicyAuthorization API.

The request URI used in each HTTP request from the NF service consumer towards the PCF shall have the structure defined in subclause 4.4.1 of 3GPP TS 29.501 [2], i.e.:

{apiRoot}/{apiName}/{apiVersion}/{apiSpecificResourceUriPart}

with the following components:

- The {apiRoot} shall be set as described in 3GPP TS 29.501 [2].
- The {apiName} shall be "npcf-policyauthorization".
- The {apiVersion} shall be "v1".
- The {apiSpecificResourceUriPart} shall be set as described in subclause 5.3.

5.2 Usage of HTTP

5.2.1 General

HTTP/2, IETF RFC 7540 [9], shall be used as specified in subclause 5.2 of 3GPP TS 29.500 [5].

HTTP/2 shall be transported as specified in subclause 5.3 of 3GPP TS 29.500 [5].

The OpenAPI [11] specification of HTTP messages and content bodies for the Npcf_PolicyAuthorization service is contained in Annex A.

5.2.2 HTTP standard headers

5.2.2.1 General

See subclause 5.2.2 of 3GPP TS 29.500 [5] for the usage of HTTP standard headers.

5.2.2.2 Content type

JSON, IETF RFC 8259 [10], shall be used as content type of the HTTP bodies specified in the present specification, as specified in subclause 5.4 of 3GPP TS 29.500 [5].

5.2.3 HTTP custom headers

The Npcf_PolicyAuthorization API shall support HTTP custom header fields specified in subclause 5.2.3.2 of 3GPP TS 29.500 [5].

In this Release of the specification, no specific custom headers are defined for the Npcf_PolicyAuthorization API.

5.3 Resources

5.3.1 Resource Structure




Figure 5.3.1-1: Resource URI structure of the Npcf_PolicyAuthorization API

Table 5.3.1-1 provides an overview of the resources and applicable HTTP methods.

Table 5.3.1-1: Resources and methods overview

Resource name	Resource URI	HTTP method or custom operation	Description
Application Sessions	//{{apiRoot}}/ npcf-policyauthorization/v1 /app-sessions	POST	Npcf_PolicyAuthorization_Create. Creates a new Individual Application Session Context resource and may create the child Events Subscription sub-resource.
Individual Application Session Context	//{{apiRoot}}/ npcf-policyauthorization/v1 /app-sessions/{{appSessionId}}	PATCH	Npcf_PolicyAuthorization_Update. Updates an existing Individual Application Session Context resource. It can also update an Events Subscription sub-resource.
		GET	Reads an existing Individual Application Session Context resource.
	//{{apiRoot}}/ npcf-policyauthorization/v1 /app-sessions/{{appSessionId}}/delete	Delete (POST)	Npcf_PolicyAuthorization_Delete. Deletes an existing Individual Application Session Context resource and the child Events Subscription sub-resource.
Events Subscription	//{{apiRoot}}/ npcf-policyauthorization/v1 /app-sessions/{{appSessionId}} /events-subscription	PUT	Npcf_PolicyAuthorization_Subscribe. Creates a new Events Subscription sub-resource or modifies an existing Events Subscription sub-resource.
		DELETE	Npcf_PolicyAuthorization_Unsubscribe. Deletes an Events Subscription sub-resource.

5.3.2 Resource: Application Sessions (Collection)

5.3.2.1 Description

The Application Sessions resource represents all application session contexts that exist in the Npcf_PolicyAuthorization service at a given PCF instance.

5.3.2.2 Resource definition

Resource URI: {apiRoot}/npcf-policyauthorization/v1/app-sessions

This resource shall support the resource URI variables defined in table 5.3.2.2-1.

Table 5.3.2.2-1: Resource URI variables for this resource

Name	Definition
apiRoot	See subclause 5.1

5.3.2.3 Resource Standard Methods

5.3.2.3.1 POST

This method shall support the URI query parameters specified in table 5.3.2.3.1-1.

Table 5.3.2.3.1-1: URI query parameters supported by the POST method on this resource

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 5.3.2.3.1-2 and the response data structures and response codes specified in table 5.3.2.3.1-3.

Table 5.3.2.3.1-2: Data structures supported by the POST Request Body on this resource

Data type	P	Cardinality	Description
AppSessionContext	M	1	Contains the information for the creation of a new Individual Application Session Context resource.

Table 5.3.2.3.1-3: Data structures supported by the POST Response Body on this resource

Data type	P	Cardinality	Response codes	Description
AppSessionContext	M	1	201 Created	Successful case. The creation of an Individual Application Session Context resource is confirmed and a representation of that resource is returned.
n/a			303 See Other	The result of the HTTP POST request would be equivalent to the existing Application Session Context. The HTTP response shall contain a Location header field set to the URI of the existing individual Application Session Context resource.
ProblemDetails	M	1	403 Forbidden	(NOTE 2)
n/a			404 Not Found	The HTTP POST request is rejected because the specified Application Session collection resource does not exist.
NOTE 1: In addition, the HTTP status codes which are specified as mandatory in table 5.2.7.1-1 of 3GPP TS 29.500 [5] for the POST method shall also apply.				
NOTE 2: Failure cases are described in subclause 5.7.				

5.3.2.4 Resource Custom Operations

None.

5.3.3 Resource: Individual Application Session Context (Document)

5.3.3.1 Description

The Individual Application Session Context resource represents a single application session context that exists in the Npcf_PolicyAuthorization service.

5.3.3.2 Resource definition

Resource URI: {apiRoot}/npcf-policyauthorization/v1/app-sessions/{appSessionId}

This resource shall support the resource URI variables defined in table 5.3.2.2-1.

Table 5.3.3.2-1: Resource URI variables for this resource

Name	Definition
ApiRoot	See subclause 5.1
appSessionId	String formatted according to IETF RFC 3986 [19] identifying an application session context.

5.3.3.3 Resource Standard Methods

5.3.3.3.1 GET

This method shall support the URI query parameters specified in table 5.3.3.3.1-1.

Table 5.3.3.3.1-1: URI query parameters supported by the GET method on this resource

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 5.3.3.3.1-2 and the response data structures and response codes specified in table 5.3.3.3.1-3.

Table 5.3.3.3.1-2: Data structures supported by the GET Request Body on this resource

Data type	P	Cardinality	Description
n/a			

Table 5.3.3.3.1-3: Data structures supported by the GET Response Body on this resource

Data type	P	Cardinality	Response codes	Description
AppSessionContext	M	1	200 OK	A representation of an Individual Application Session Context resource is returned.
ProblemDetails	M	1	404 Not Found	(NOTE 2)
NOTE 1: In addition, the HTTP status codes which are specified as mandatory in table 5.2.7.1-1 of 3GPP TS 29.500 [5] for the GET method shall also apply.				
NOTE 2: Failure cases are described in subclause 5.7.				

5.3.3.3.2 PATCH

This method shall support the URI query parameters specified in table 5.3.3.3.2-1.

Table 5.3.3.3.2-1: URI query parameters supported by the PATCH method on this resource

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 5.3.3.3.2-2 and the response data structures and response codes specified in table 5.3.3.3.2-3.

Table 5.3.3.3.2-2: Data structures supported by the PATCH Request Body on this resource

Data type	P	Cardinality	Description
AppSessionContextUpdateData	M	1	Contains the modification(s) to apply to the Individual Application Session Context resource.

Table 5.3.3.3.2-3: Data structures supported by the PATCH Response Body on this resource

Data type	P	Cardinality	Response codes	Description
AppSessionContext	M	1	200 OK	Successful case. The Individual Application Session Context resource was modified and a representation of that resource is returned.
n/a			204 No Content	Successful case. The Individual Application session context resource was modified.
ProblemDetails	M	1	403 Forbidden	(NOTE 2)
ProblemDetails	M	1	404 Not Found	(NOTE 2)
NOTE 1: In addition, the HTTP status codes which are specified as mandatory in table 5.2.7.1-1 of 3GPP TS 29.500 [5] for the PATCH method shall also apply.				
NOTE 2: Failure cases are described in subclause 5.7.				

5.3.3.4 Resource Custom Operations

5.3.3.4.1 Overview

Table 5.3.3.4.1-1: Custom operations

Custom operation URI	Mapped HTTP method	Description
://{apiRoot}/ npcf-policyauthorization/v1 /app-sessions/{appSessionId}/delete	POST	Npcf_PolicyAuthorization_Delete. Deletes an existing Individual Application Session Context resource and the child Events Subscription sub-resource.

5.3.3.4.2 Operation: delete

5.3.3.4.2.1 Description

5.3.3.4.2.2 Operation Definition

This custom operation deletes an existing Individual Application Session Context resource and the child Events Subscription sub-resource in the PCF.

This operation shall support the request data structures specified in table 5.3.3.4.2.2-1 and the response data structure and response codes specified in table 5.3.3.4.2.2-2.

Table 5.3.3.4.2.2-1: Data structures supported by the POST Request Body on this resource

Data type	P	Cardinality	Description
EventsSubscReqData	O	0..1	Events subscription information to be sent by the AF to request event notification when the Individual Application Session Context resource is deleted.

Table 5.3.3.4.2.2-2: Data structures supported by the POST Response Body on this resource

Data type	P	Cardinality	Response codes	Description
n/a			204 No Content	Successful case. The Individual Application session context resource was deleted.
EventsNotification	M	1	200 OK	Successful case. The Individual Application Session Context resource was deleted and a partial representation of that resource containing event notification information is returned.
ProblemDetails	M	1	404 Not Found	(NOTE 2)
NOTE 1: In addition, the HTTP status codes which are specified as mandatory in table 5.2.7.1-1 of 3GPP TS 29.500 [5] for the POST method shall also apply.				
NOTE 2: Failure cases are described in subclause 5.7.				

5.3.4 Resource: Events Subscription (Document)

5.3.4.1 Description

The Events Subscription sub-resource represents a subscription to events for an application session context that exists in the Npcf_PolicyAuthorization service.

5.3.4.2 Resource definition

Resource URI: {apiRoot}/npcf-policyauthorization/v1/app-sessions/{appSessionId}/events-subscription

This resource shall support the resource URI variables defined in table 5.3.4.2-1.

Table 5.3.4.2-1: Resource URI variables for this resource

Name	Definition
ApiRoot	See subclause 5.1
appSessionId	String formatted according to IETF RFC 3986 [19] identifying an application session context

5.3.4.3 Resource Standard Methods

5.3.4.3.1 PUT

This method shall support the URI query parameters specified in table 5.3.4.3.1-1.

Table 5.3.4.3.1-1: URI query parameters supported by the PUT method on this resource

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 5.3.4.3.1-2 and the response data structures and response codes specified in table 5.3.4.3.1-3.

Table 5.3.4.3.1-2: Data structures supported by the PUT Request Body on this resource

Data type	P	Cardinality	Description
EventsSubscReqData	M	1	Contains information for the modification of the Events Subscription sub-resource.

Table 5.3.4.3.1-3: Data structures supported by the PUT Response Body on this resource

Data type	P	Cardinality	Response codes	Description
EventsNotification	O	0..1	201 Created	Successful case. The Events Subscription sub-resource was created and events notification data is included.
EventsNotification	O	0..1	200 OK	Successful case. The Events Subscription sub-resource was modified and events notification data is included.
EventsSubscReqData	M	1	201 Created	Successful case. The Events Subscription sub-resource was created.
EventsSubscReqData	M	1	200 OK	Successful case. The Events Subscription sub-resource was modified and a representation of that sub-resource is returned.
n/a			204 No Content	Successful case. The Events Subscription sub-resource was modified.
ProblemDetails	M	1	403 Forbidden	(NOTE 2)
ProblemDetails	M	1	404 Not Found	(NOTE 2)
NOTE 1: In addition, the HTTP status codes which are specified as mandatory in table 5.2.7.1-1 of 3GPP TS 29.500 [5] for the PUT method shall also apply.				
NOTE 2: Failure cases are described in subclause 5.7.				

5.3.4.3.2 DELETE

This method shall support the URI query parameters specified in table 5.3.4.3.2-1.

Table 5.3.4.3.2-1: URI query parameters supported by the DELETE method on this resource

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 5.3.4.3.2-2 and the response data structures and response codes specified in table 5.3.4.3.2-3.

Table 5.3.4.3.2-2: Data structures supported by the DELETE Request Body on this resource

Data type	P	Cardinality	Description
n/a			

Table 5.3.4.3.2-3: Data structures supported by the DELETE Response Body on this resource

Data type	P	Cardinality	Response codes	Description
n/a			204 No Content	Successful case. The Events Subscription sub-resource was deleted.
ProblemDetails	M	1	404 Not Found	(NOTE 2)
NOTE 1: In addition, the HTTP status codes which are specified as mandatory in table 5.2.7.1-1 of 3GPP TS 29.500 [5] for the DELETE method shall also apply.				
NOTE 2: Failure cases are described in subclause 5.7.				

5.3.3.4 Resource Custom Operations

None.

5.4 Custom Operations without associated resources

No custom operation is defined in this Release of the specification.

5.5 Notifications

5.5.1 General

Notifications shall comply to subclause 6.2 of 3GPP TS 29.500 [5] and subclause 4.6.2.3 of 3GPP TS 29.501 [6].

Table 5.5.1-1: Notifications

Custom operation URI	Mapped HTTP method	Description
{notifUri}/notify	POST	PCF event notification.
{notifUri}/terminate	POST	Request for termination of the Individual Application Session Context.

5.5.2 Event Notification

5.5.2.1 Description

The Event Notification is used by the PCF to report one or several observed application session context events to the NF service consumer that has subscribed to such notifications via the Events Subscription sub-resource.

5.5.2.2 Target URI

The Notification URI "{notifUri}/notify" shall be used with the URI variables defined in table 5.5.2.2-1.

Table 5.5.2.2-1: URI variables

Name	Definition
notifUri	String formatted as URI with the Notification Uri as assigned within the Events Subscription sub-resource and described within the EventsSubscriptionData type (see table 5.6.2.6-1).

5.5.2.3 Standard Methods

5.5.2.3.1 POST

This method shall support the URI query parameters specified in table 5.5.2.3.1-1.

Table 5.5.2.3.1-1: URI query parameters supported by the POST method on this resource

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 5.5.2.3.1-2 and the response data structures and response codes specified in table 5.5.2.3.1-3.

Table 5.5.2.3.1-2: Data structures supported by the POST Request Body on this resource

Data type	P	Cardinality	Description
EventsNotification	M	1	Provides Information about observed events

Table 5.5.2.3.1-3: Data structures supported by the POST Response Body on this resource

Data type	P	Cardinality	Response codes	Description
n/a			204 No Content	The receipt of the Notification is acknowledged.
NOTE: In addition, the HTTP status codes which are specified as mandatory in table 5.2.7.1-1 of 3GPP TS 29.500 [5] for the POST method shall also apply.				

5.5.3 Termination Request

5.5.3.1 Description

The Termination Request is used by the PCF to request the NF service consumer the deletion of the Individual Application Session Context resource.

5.5.3.2 Target URI

The Notification URI "{notifUri}/terminate" shall be used with the URI variables defined in table 5.5.3.2-1.

Table 5.5.3.2-1: URI variables

Name	Definition
notifUri	String formatted as URI with the Notification Uri as assigned within the Individual Application Session Context-resource and described within the AppSessionContextReqData Data type (see table 5.6.2.3-1).

5.5.3.3 Standard Methods

5.5.3.3.1 POST

This method shall support the URI query parameters specified in table 5.5.3.3.1-1.

Table 5.5.3.3.1-1: URI query parameters supported by the POST method on this resource

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 5.5.3.3.1-2 and the response data structures and response codes specified in table 5.5.3.3.1-3.

Table 5.5.3.3.1-2: Data structures supported by the POST Request Body on this resource

Data type	P	Cardinality	Description
TerminationInfo	M	1	Provides information about the deletion of the resource.

Table 5.5.3.3.1-3: Data structures supported by the POST Response Body on this resource

Data type	P	Cardinality	Response codes	Description
n/a			204 No Content	The receipt of the Notification is acknowledged.
NOTE: In addition, the HTTP status codes which are specified as mandatory in table 5.2.7.1-1 of 3GPP TS 29.500 [5] for the POST method shall also apply.				

5.6 Data Model

5.6.1 General

This subclause specifies the application data model supported by the API.

Table 5.6.1-1 specifies the data types defined for the Npcf_PolicyAuthorization service based interface protocol.

Table 5.6.1-1: Npcf_PolicyAuthorization specific Data Types

Data type	Section defined	Description	Applicability
AccessNetChargingAddress	5.6.2.18	Indicates the IP address of the network entity within the access network performing charging.	
AccessNetChargingIdentifier	5.6.2.19	Contains a charging identifier.	
AfEvent	5.6.3.7	Represents an event to notify to the AF.	
AfEventNotification	5.6.2.11	Represents the notification of an event.	
AfEventSubscription	5.6.2.10	Represents the subscription to events.	
AfNotifMethod	5.6.3.8	Represents the notification methods that can be subscribed for an event.	
AfRoutingRequirement	5.6.2.13	Describes the routing requirements for the application traffic flows.	Influence on Traffic Routing
AnGwAddress	5.6.2.20	Carries the control plane address of the access network gateway.	
AppSessionContext	5.6.2.2	Represents an Individual Application Session Context resource.	
AppSessionContextReqData	5.6.2.3	Represents the Individual Application Session Context resource data received in an HTTP POST request message.	
AppSessionContextRespData	5.6.2.4	Represents the Individual Application Session Context resource data produced by the server and returned in an HTTP response message.	
AppSessionContextUpdateData	5.6.2.5	Describes the modifications to an Individual Application Session Context resource.	
EventsNotification	5.6.2.9	Describes the notification about the events occurred within an Individual Application Session Context resource.	
EventsSubscReqData	5.6.2.6	Identifies the events the application subscribes to within an Individual Application Session Context resource.	
EthFlowDescription	5.6.2.17	Defines a packet filter for an Ethernet flow.	
FlowDescription	5.6.3.2	Defines a packet filter for an IP flow.	
Flows	5.6.2.21	Identifies the flows related to a media component.	
MediaComponent	5.6.2.7	Contains service information for a media component of an AF session.	
MediaComponentStatus	5.6.3.x1	Indicates whether the PCC rules related to a media component are active or inactive.	
MediaSubComponent	5.6.2.8	Contains the requested bitrate and filters for the set of IP flows identified by their common flow identifier.	
QosNotifType	5.6.3.9	Indicates type of notification for QoS Notification Control.	
RequiredAccessInfo	5.6.3.11	Indicates the access network information required for an AF session.	NetLoc
RouteInformation	5.6.2.15	IP address and UDP port of the tunnel end point in the data network.	Influence on Traffic Routing
RouteToLocation	5.6.2.14	Describes the traffic routes to the locations of the application.	Influence on Traffic Routing
ServAuthInfo	5.6.3.5	Indicates the result of the Policy Authorization service request from the AF.	
SpatialValidity	5.6.2.16	Describes the spatial validity of an AF request for influencing traffic routing.	Influence on Traffic Routing
SponId	5.6.3.2	Contains an Identity of a sponsor.	Sponsored Connectivity
SponsoringStatus	5.6.3.6	Represents whether sponsored data connectivity is enabled or disabled/not enabled.	Sponsored Connectivity
TerminationCause	5.6.3.10	Indicates the cause for requesting the deletion of the Individual Application Session Context resource.	
TerminationInfo	5.6.2.12	Includes information related to the termination of the Individual Application Session Context resource.	

Table 5.6.1-2 specifies data types re-used by the Npcf_PolicyAuthorization service based interface protocol from other specifications, including a reference to their respective specifications and when needed, a short description of their use within the Npcf_PolicyAuthorization service based interface.

Table 5.6.1-2: Npcf_PolicyAuthorization re-used Data Types

Data type	Reference	Comments	Applicability
AccumulatedUsage	3GPP TS 29.122 [15]	Accumulated Usage.	Sponsored Connectivity
BdtReferenceId	3GPP TS 29.122 [15]	Identifies transfer policies.	
BitRate	3GPP TS 29.571 [12]	Specifies bitrate in kbits per second.	
DateTime	3GPP TS 29.571 [12]	String with format "date-time" as defined in OpenAPI Specification [11].	
DateTime	3GPP TS 29.571 [12]	Time	NetLoc
Dnai	3GPP TS 29.571 [12]	Data network access identifier.	Influence on Traffic Routing
DnaiChangeType	3GPP TS 29.508 [13]	Describes the types of DNAI change.	Influence on Traffic Routing
Dnn	3GPP TS 29.571 [12]		
FlowDirection	3GPP TS 29.512 [8]	Flow Direction.	
FlowStatus	3GPP TS 29.512 [8]		
Ipv4Addr	3GPP TS 29.571 [12]		
Ipv6Addr	3GPP TS 29.571 [12]		
MacAddr48	3GPP TS 29.571 [12]	MAC Address.	
PlmnId	3GPP TS 29.571 [12]	PLMN mobile country code and mobile network code.	NetLoc
PraElement	3GPP TS 29.571 [12]	Represents a Presence Reporting Area.	Influence on Traffic Routing
RatType	3GPP TS 29.571 [12]	RAT Type.	
Snsai	3GPP TS 29.571 [12]	Identifies the S-NSSAI.	
Supi	3GPP TS 29.571 [12]		
SupportedFeatures	3GPP TS 29.571 [12]	Used to negotiate the applicability of the optional features defined in table 5.8-1.	
TimeZone	3GPP TS 29.571 [12]	Time Zone.	NetLoc
UInteger	3GPP TS 29.571 [12]	Unsigned Integer, i.e. only value 0 and integers above 0 are permissible. In an OpenAPI Specification [11] schema, the format shall be designated as "UInteger".	
UsageThreshold	3GPP TS 29.122 [15]	Usage Thresholds.	Sponsored Connectivity
UserLocation	3GPP TS 29.571 [12]	User Location.	NetLoc

5.6.2 Structured data types

5.6.2.1 Introduction

This subclause defines the structures to be used in resource representations.

Allowed structures are: array, object.

5.6.2.2 Type AppSessionContext

Table 5.6.2.2-1: Definition of type AppSessionContext

Attribute name	Data type	P	Cardinality	Description	Applicability
ascReqData	AppSessionContextReqData	C	0..1	Identifies the service requirements of an Individual Application Session Context. It shall be present in HTTP POST request messages and may be included in the HTTP response messages.	
ascRespData	AppSessionContextRespData	C	0..1	Describes the authorization data of an Individual Application Session Context created by the PCF. It may be present in the HTTP response messages.	
evsNotif	EventsNotification	O	0..1	Describes information related to the notification of events.	

5.6.2.3 Type AppSessionContextReqData

Table 5.6.2.3-1: Definition of type AppSessionContextReqData

Attribute name	Data type	P	Cardinality	Description	Applicability
afAppld	AfAppld	O	0..1	AF application identifier.	
afChargId	AfChargingId	O	0..1	AF charging identifier. This information may be used for charging correlation with QoS flow.	
afRoutReq	AfRoutingRequirement	O	0..1	Indicates the AF traffic routing requirements.	Influence on Traffic Routing
aspld	Aspld	C	0..1	Application service provider identity.	Sponsored Connectivity
bdtRefId	BdtReferenceId	O	0..1	Reference to a transfer policy negotiated for background data traffic.	
dnn	Dnn	O	0..1	Data Network Name.	
evSubsc	EventsSubscReqData	O	0..1	Identifies the events the application subscribes to at creation or modification of an Individual Application Session Context resource.	
medComponents	map(MediaComponent)	O	0..N	Media Component information. The key of the map is the attribute "medCompN".	
notifUri	Link	M	1	Notification URI for Application Session Context termination requests.	
slicInfo	Snsai	O	0..1	Identifies the S-NSSAI.	
sponId	SponId	C	0..1	Sponsor identity.	Sponsored Connectivity
sponStatus	SponsoringStatus	O	0..1	Indication of whether sponsored connectivity is enabled or disabled/not enabled. The absence of the attribute indicates that the sponsored connectivity is enabled.	Sponsored Connectivity
supi	Supi	O	0..1	Subscription Permanent Identifier.	
supportedFeatures	SupportedFeatures	O	0..1	This IE represents a list of Supported features used as described in subclause 5.8. It may be supplied by the NF service consumer in the POST request that request a creation of an Individual Application Session Context resource. It shall be supplied by the PCF in the response if supplied in the POST request.	
ueIpv4	Ipv4Addr	C	0..1	The IPv4 Address of the served UE.	
ueIpv6	Ipv6Addr	C	0..1	The IPv6 Address of the served UE.	
ueMac	MacAddr48	C	0..1	The MAC Address of the served UE.	

5.6.2.4 Type AppSessionContextRespData

Table 5.6.2.4-1: Definition of type AppSessionContextRespData

Attribute name	Data type	P	Cardinality	Description	Applicability
servAuthInfo	ServAuthInfo	O	0..1	Indicates the result of the authorization for a service request bound to a transfer policy.	

5.6.2.5 Type AppSessionContextUpdateData

Table 5.6.2.5-1: Definition of type AppSessionContextUpdateData

Attribute name	Data type	P	Cardinality	Description	Applicability
afAppld	AfAppld	O	0..1	AF application identifier.	
aspId	AspId	O	0..1	Application service provider identity.	Sponsored Connectivity
bdtRefId	BdtReferencId	O	0..1	Reference to a transfer policy negotiated for background data traffic.	
evSubsc	EventsSubscReqData	O	0..1	Identifies the events the application subscribes to at modification of an Individual Application Session Context resource.	
medComponents	map(MediaComponent)	O	0..N	Media Component information.	
sponId	SponId	O	0..1	Sponsor identity.	Sponsored Connectivity
sponStatus	SponsoringStatus	O	0..1	Indication of whether sponsored connectivity is enabled or disabled/not enabled. The absence of the attribute indicates that the sponsored connectivity is enabled.	Sponsored Connectivity

5.6.2.6 Type EventsSubscReqData

Table 5.6.2.6-1: Definition of type EventsSubscReqData

Attribute name	Data type	P	Cardinality	Description	Applicability
dnaiChgType	DnaiChangeType	C	0..1	Indicates the type of DNAI change. It shall be present when the subscribed event is "DNAI_CHG".	Influence on Traffic Routing
events	array(AfEventSubscription)	M	1..N	Subscribed Events.	
notifUri	Link	O	0..1	Notification URI.	
reqAni	RequiredAccessInfo	C	0..1	Represents the required access network information. It shall be present when the event "ANI_REPORT" is subscribed.	NetLoc
usgThres	UsageThreshold	O	0..1	Includes the volume and/or time thresholds for sponsored data connectivity.	Sponsored Connectivity

Editor's note: It is FFS the complete set of attributes and data types to be supported by the EventsSubscReqData data type.

5.6.2.7 Type MediaComponent

Table 5.6.2.7-1: Definition of type MediaComponent

Attribute name	Data type	P	Cardinality	Description	Applicability
afAppld	AfAppld	O	0..1	Contains information that identifies the particular service the AF session belongs to.	
afRoutReq	AfRoutingRequirement	O	0..1	Indicates the AF traffic routing requirements.	Influence on Traffic Routing
medCompN	Integer	M	1	Identifies the media component number, and it contains the ordinal number of the media component.	
medSubComps	map(MediaSubComponent)	O	0..N	Contains the requested bitrate and filters for the set of IP flows identified by their common flow identifier. The key of the map is the attribute "fNum".	
medType	MediaType	O	0..1	Indicates the media type of the service.	
marBwUl	BitRate	O	0..1	Maximum requested bandwidth for the Uplink.	
marBwDl	BitRate	O	0..1	Maximum requested bandwidth for the Downlink.	
mirBwUl	BitRate	O	0..1	Minimum requested bandwidth for the Uplink.	
mirBwDl	BitRate	O	0..1	Minimum requested bandwidth for the Downlink.	
fStatus	FlowStatus	O	0..1	Indicates whether the status of the IP flows is enabled, or disabled.	
resPrio	ReservPriority	O	0..1	Indicates the reservation priority.	
codecs	array(CodecData)	O	0..2	Indicates the codec data.	

All IP flows within a "MediaSubComponent" data type are permanently disabled by supplying "FlowStatus" data type with a deletion indication.

5.6.2.8 Type MediaSubComponent

Table 5.6.2.8-1: Definition of type MediaSubComponent

Attribute name	Data type	P	Cardinality	Description	Applicability
ethfDescs	array(EthFlowDescription)	O	0..2	Contains the flow description for the Uplink and/or Downlink Ethernet flows.	
fNum	Integer	M	1	Identifies the ordinal number of the IP flow.	
fDescs	array(FlowDescription)	O	0..2	Contains the flow description for the Uplink and/or Downlink IP flows.	
fStatus	FlowStatus	O	0..1	Indicates whether the status of the service data flows is enabled or disabled.	
marBwUl	BitRate	O	0..1	Maximum requested bandwidth for the Uplink.	
marBwDl	BitRate	O	0..1	Maximum requested bandwidth for the Downlink.	
tosTrCl	TosTrafficClass	O	0..1	Type of Service or Traffic Class.	

The bit rate information and flow status information provided within the "MediaSubComponent" data type takes precedence over information provided within "MediaComponent" data type.

All service data flows within a "MediaSubComponent" data type are permanently disabled by supplying "FlowStatus" data type with a deletion indication.

5.6.2.9 Type EventsNotification

Table 5.6.2.9-1: Definition of type EventsNotification

Attribute name	Data type	P	Cardinality	Description	Applicability
accessType	AccessType	C	0..1	Includes the access type. It shall be present when the notified event is "ACCESS_TYPE_CHG".	
anChargAddr	AccessNetChargingAddress	O	0..1	Includes the access network charging address. It shall be present if available when the notified event is "CHARGING_CORRELATION".	
anChargIds	array(AccessNetChargingIdentifier)	C	0..N	Includes the access network charging identifier(s). It shall be present when the notified event is "CHARGING_CORRELATION".	
anGwAddr	AnGwAddress	O	0..1	Access network Gateway Address. It shall be present, if applicable, when the notified event is "ACCESS_TYPE_CHG".	
evSubsUri	Link	M	1	The Events Subscription URI. Identifies the Events Subscription sub-resource that triggered the notification.	
evNotif	array(AfEventNotification)	M	1..N	Notifications about individual events.	
netLocAccSupp	NetLocAccSupp	O	0..1	Indication of whether the access network supports access network information reporting. The absence of this attribute indicates the access network supports access network information reporting.	NetLoc
plmnCcNc	PlmnId	O	0..1	Serving PLMN mobile country code and mobile network code.	
plmnId	PlmnId	C	0..1	PLMN Identifier. It shall be present when the notified event is "PLMN_CHG".	
ratType	RatType	O	0..1	RAT type. It shall be present, if applicable, when the notified event is "ACCESS_TYPE_CHG".	
ueLoc	UserLocation	O	0..1	E-UTRA, NR, or non-3GPP access user location information.	NetLoc
ueLocTime	DateTime	O	0..1	The time user location information was last known.	NetLoc
ueTimeZone	TimeZone	O	0..1	UE time zone.	NetLoc
usgRep	AccumulatedUsage	C	0..1	Indicates the measured volume and/or time for sponsored data connectivity. It shall be present when the notified event is "USAGE_REPORT".	Sponsored Connectivity

5.6.2.10 Type AfEventSubscription

Table 5.6.2.10-1: Definition of type AfEventSubscription

Attribute name	Data type	P	Cardinality	Description	Applicability
event	AfEvent	M	1	Subscribed Event.	
notifMethod	AfNotifMethod	O	0..1	If notifMethod is not supplied, the default value "EVENT_DETECTION" applies.	

5.6.2.11 Type AfEventNotification

Table 5.6.2.11-1: Definition of type AfEventNotification

Attribute name	Data type	P	Cardinality	Description	Applicability
event	AfEvent	M	1	Notified Event.	
flows	array(Flows)	O	0..N	Affected Service Data Flows.	
notifType	QosNotifType	O	0..1	Indication of type of notification for QoS Notification Control.	

5.6.2.12 Type TerminationInfo

Table 5.6.2.12-1: Definition of type TerminationInfo

Attribute name	Data type	P	Cardinality	Description	Applicability
termCause	TerminationCause	M	1	Indicates the cause for requesting the deletion of the Individual Application Session Context resource.	
resUri	Link	M	1	Identifies the Individual Application Session Context.	

5.6.2.13 Type AfRoutingRequirement

Table 5.6.2.13-1: Definition of type AfRoutingRequirement

Attribute name	Data type	P	Cardinality	Description	Applicability
appReloc	boolean	O	0..1	Indication of application relocation possibility.	Influence on traffic routing
routeToLocs	array(RouteToLocation)	O	0..N	A list of traffic routes to applications locations.	Influence on traffic routing
spVal	SpatialValidity	O	0..1	Indicates where the traffic routing requirements apply. The absence of this attribute indicates no spatial restrictions.	Influence on traffic routing
startTime	DateTime	O	0..1	Indicates the time from which the traffic routing requirements start to apply. The absence of this attribute indicates the traffic routing requirements apply immediately.	Influence on traffic routing
stopTime	DateTime	O	0..1	Indicates the time when the traffic routing requirements cease to apply. The absence of this attribute indicates the traffic routing requirements do not cease at any time.	Influence on traffic routing

5.6.2.14 Type RouteToLocation

Table 5.6.2.14-1: Definition of type RouteToLocation

Attribute name	Data type	P	Cardinality	Description	Applicability
dnai	Dnai	M	1	Identifies the location of the application.	Influence on Traffic Routing
routeInfo	RouteInformation	C	0..1	Includes the traffic routing information.	Influence on Traffic Routing
routeProfileId	string	C	0..1	Identifies the routing profile Id.	Influence on Traffic Routing
NOTE: Either the "routeInfo" attribute or the "routeProfileId" attribute shall be included in the "RouteToLocation" data type.					

5.6.2.15 Type RouteInformation

Table 5.6.2.15-1: Definition of type RouteInformation

Attribute name	Data type	P	Cardinality	Description	Applicability
ipv6Addr	Ipv6Addr	M	1	Ipv6 address of the tunnel end point in the data network.	Influence on Traffic Routing
portNumber	UInteger	M	1	UDP port number of the tunnel end point in the data network.	Influence on Traffic Routing

5.6.2.16 Type SpatialValidity

Table 5.6.2.16-1: Definition of type SpatialValidity

Attribute name	Data type	P	Cardinality	Description	Applicability
pralids	array(string)	O	0..N	List of PRA identifiers.	Influence on Traffic Routing
praElements	array(PraElement)	O	0..N	List of PRA elements.	Influence on Traffic Routing

5.6.2.17 Type EthFlowDescription

Table 5.6.2.17-1: Definition of type EthFlowDescription

Attribute name	Data type	P	Cardinality	Description	Applicability
destMacAddr	MacAddr48	O	0..1	Destination MAC address.	
ethType	string	M	0..1	A two-octet string that represents the EtherType, as described in IEEE 802.3 [16] and IETF RFC 7042 [18] in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the EtherType shall appear first in the string, and the character representing the 4 least significant bits of the EtherType shall appear last in the string.	
fDesc	FlowDescription	C	0..1	Contains the flow description for the Uplink or Downlink IP flow. It shall be present when the EtheType is IP.	
fDir	FlowDirection	O	0..1	Contains the packet filter direction.	
sourceMacAddr	MacAddr48	O	0..1	Source MAC address.	
vlanTags	array(string)	O	0..2	Customer-VLAN and/or Service-VLAN tags containing the VID, PCP/DEI fields as defined in IEEE 802.1Q [17] and IETF RFC 7042 [18]. Each field is encoded as a two-octet string in hexadecimal representation. Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the VID or PCF/DEI field shall appear first in the string, and the character representing the 4 least significant bits of the VID or PCF/DEI field shall appear last in the string.	

NOTE: The EtherFlowDescription data type allows any combination of the defined properties.

5.6.2.18 Type AccessNetChargingAddress

Table 5.6.2.18-1: Definition of type AccessNetChargingAddress

Attribute name	Data type	P	Cardinality	Description	Applicability
anChargIpv4Addr	Ipv4Addr	O	0..1	Includes the IPv4 address of network entity within the access network performing charging.	
anChargIpv6Addr	Ipv6Addr	O	0..1	Includes the IPv6 address of network entity within the access network performing charging.	

NOTE: Either the IPv4 or the IPv6 address of the access network node shall be included.

5.6.2.19 Type AccessNetChargingIdentifier

Table 5.6.2.19-1: Definition of type AccessNetChargingIdentifier

Attribute name	Data type	P	Cardinality	Description	Applicability
anChargIdValue	string	M	1	Contains a charging identifier.	
flows	array(Flows)	O	0..N	information about the flows transported within the corresponding QoS flow. If no flows are provided, the charging identifier applies for all flows within the AF session.	

5.6.2.20 Type AnGwAddress

Table 5.6.2.20-1: Definition of type AnGwAddress

Attribute name	Data type	P	Cardinality	Description	Applicability
anGwIpv4addr	Ipv4Addr	O	0..1	Includes the IPv4 address of the access network gateway control node.	
anGwIpv6addr	Ipv6Addr	O	0..1	Includes the IPv6 address of the access network gateway control node.	

NOTE: Either the IPv4 and/or the IPv6 address (if available) of the access network gateway control node shall be included.

5.6.2.21 Flows

Table 5.6.2.21-1: Definition of type Flows

Attribute name	Data type	P	Cardinality	Description	Applicability
fNums	array(integer)	O	0..N	Indicates the service data flows via their flow identifier. If no flow identifier is supplied, the Flows data type refers to all the flows matching the media component number.	
medCompN	integer	M	1	Identifies the media component number, and it contains the ordinal number of the media component.	

5.6.3 Simple data types and enumerations

5.6.3.1 Introduction

This subclause defines simple data types and enumerations that can be referenced from data structures defined in the previous subclauses.

5.6.3.2 Simple data types

The simple data types defined in table 5.6.3.2-1 shall be supported.

Table 5.6.3.2-1: Simple data types

Type Name	Type Definition	Description	Applicability
AfAppId	string	Contains an AF application identifier.	
AspId	string	Contains an identity of an application service provider.	Sponsored Connectivity
CodecData	string	Contains codec related information. Refer to subclause 5.3.7 of 3GPP TS 29.214 [20] for encoding.	
FlowDescription	string	Defines a packet filter for an IP flow. Refer to subclause 5.3.8 of 3GPP TS 29.214 [20] for encoding.	
NetLocAccSupp	boolean	Indication of whether the access network supports access network information reporting.	NetLoc
SponId	string	Contains an identity of a sponsor.	Sponsored Connectivity

5.6.3.3 Enumeration: MediaType

The enumeration "MediaType" represents the media type of a media component.

Table 5.6.3.3-1: Enumeration MediaType

Enumeration value	Description	Applicability
AUDIO	The type of media is audio.	
VIDEO	The type of media is video.	
DATA	The type of media is data.	
APPLICATION	The type of media is application data.	
CONTROL	The type of media is control.	
TEXT	The type of media is text.	
MESSAGE	The type of media is message	
OTHER	Other type of media.	

5.6.3.4 Enumeration: ReservPriority

The enumeration "ReservPriority" represents the reservation priority. The lowest priority shall be indicated with the "PRIO_1" value, the next after the lowest with the "PRIO_2" value, and so on up to the highest priority which shall be indicated with "PRIO_16".

Table 5.6.3.4-1: Enumeration ReservPriority

Enumeration value	Description	Applicability
PRIO_1		
PRIO_2		
PRIO_3		
PRIO_4		
PRIO_5		
PRIO_6		
PRIO_7		
PRIO_8		
PRIO_9		
PRIO_10		
PRIO_11		
PRIO_12		
PRIO_13		
PRIO_14		
PRIO_15		
PRIO_16		

5.6.3.5 Enumeration: ServAuthInfo

The enumeration "servAuthInfo" represents the result of the Npcf_PolicyAuthorization service request from the AF.

Table 5.6.3.5-1: Enumeration ServAuthInfo

Enumeration value	Description	Applicability
TP_NOT_KNOWN	Indicates the transfer policy is not known.	
TP_EXPIRED	Indicates the transfer policy has expired.	
TP_NOT_YET_OCCURRED	Indicates the time window of the transfer policy has not yet occurred.	
UNAUTH_TRAFFIC_ROUTING_REQ	Indicates the traffic routing request is not authorized.	Influence on Traffic Routing

5.6.3.6 Enumeration: SponsoringStatus

The enumeration "SponsoringStatus" represents whether the sponsored data connectivity is enabled or disabled/not-enabled.

Table 5.6.3.6-1: Enumeration SponsoringStatus

Enumeration value	Description	Applicability
SPONSOR_DISABLED	Sponsored data connectivity is disabled or not enabled.	Sponsored Connectivity
SPONSOR_ENABLED	Sponsored data connectivity is enabled.	Sponsored Connectivity

5.6.3.7 Type AfEvent

The enumeration "AfEvent" represents the traffic events the PCF can notify to the AF.

Table 5.6.3.7-1: Enumeration AfEvent

Enumeration value	Description	Applicability
ACCESS_TYPE_CHG	Access type change.	
ANI_REPORT	Access Network Report requested.	NetLoc
CHARGING_CORRELATION	Access network charging correlation.	
DNAI_CHG	DNAI change.	Influence on Traffic Routing
FAILED_RESOURCES_ALLOCATION	One or more of the SDFs of an Individual Application Session Context are deactivated at the SMF.	
PLMN_CHG	This trigger indicates PLMN change.	
QOS_NOTIF_CONTROL	The GBR QoS targets of a SDF are not fulfilled or are fulfilled again.	
ROUT_REQ_STATUS_CHG	AF traffic routing requirements status change.	Influence on Traffic Routing
USAGE_REPORT	Volume and/or time usage for sponsored data connectivity.	Sponsored Connectivity

5.6.3.8 Type AfNotifMethod

The enumeration "AfNotifMethod" represents the notification methods that can be subscribed by an AF.

Table 5.6.3.8-1: Enumeration AfNotifMethod

Enumeration value	Description	Applicability
EVENT_DETECTION	Event is reported whenever the event is met and the subscription is alive.	
ONE_TIME	Events are reported once the event is met and are not reported again unless the AF refreshes the subscription.	

5.6.3.9 Type QosNotifType

The enumeration "QosNotifType" represents the types of reports bound to the notification of QoS Notification Control.

Table 5.6.3.9-1: Enumeration QosNotifType

Enumeration value	Description	Applicability
FULFILLED	The QoS targets of one or more SDFs are fulfilled again.	
NOT_FULFILLED	The QoS targets of one or more SDFs are not being fulfilled.	

5.6.3.10 Type TerminationCause

The enumeration "TerminationCause" represents the types of causes the PCF can report when requesting to the AF the deletion of the "Individual Application Session Context" resource.

Table 5.6.3.10-1: Enumeration TerminationCause

Enumeration value	Description	Applicability
ALL_SDF_DEACTIVATION	All the SDFs of an Individual Application Session Context are deactivated at the SMF.	
PDU_SESSION_TERMINATION	The PDU session is terminated.	

5.6.3.11 Type RequiredAccessInfo

The enumeration "RequiredAccessInfo" represents the access network information required for the "Individual Application Session Context" resource.

Table 5.6.3.11-1: Enumeration RequiredAccessInfo

Enumeration value	Description	Applicability
USER_LOCATION	Indicates that the user location information shall be reported.	
MS_TIME_ZONE	Indicates that the user timezone shall be reported.	

5.7 Error handling

5.7.1 General

HTTP error handling shall be supported as specified in subclause 5.2.4 of 3GPP TS 29.500 [5].

For the Npcf_PolicyAuthorization API, HTTP error responses shall be supported as specified in subclause 4.8 of 3GPP TS 29.501 [6]. Protocol errors and application errors specified in table 5.2.7.2-1 of 3GPP TS 29.500 [5] shall be supported for an HTTP method if the corresponding HTTP status codes are specified as mandatory for that HTTP method in table 5.2.7.1-1 of 3GPP TS 29.500 [5]. In addition, the requirements in the following subclauses shall apply.

5.7.2 Protocol Errors

In this Release of the specification, there are no additional protocol errors applicable for the Npcf_PolicyAuthorization API.

5.7.3 Application Errors

The application errors defined for the Npcf_PolicyAuthorization API are listed in table 5.7.3-1. The PCF shall include in the HTTP status code a "ProblemDetails" data structure with the "cause" attribute indicating the application error as listed in table 5.7.3-1.

Table 5.7.3-1: Application errors

Application Error	HTTP status code	Description
REQUESTED_SERVICE_NOT_AUTHORIZED	403 Forbidden	The service information provided in the request is rejected. (NOTE 1)
REQUESTED_SERVICE_TEMPORARILY_NOT_AUTHORIZED	403 Forbidden	The service information provided in the request is temporarily rejected. (NOTE 2)
UNAUTHORIZED_SPONSORED_DATA_CONNECTIVITY	403 Forbidden	The request for sponsored data connectivity is not authorized. (NOTE 3)
UNAUTHORIZED_TRAFFIC_ROUTING_REQUEST	403 Forbidden	The request for traffic routing is not authorized. (NOTE 4)
APPLICATION_SESSION_CONTEXT_NOT_FOUND	404 Not Found	The HTTP request is rejected because the specified Individual Application Session Context does not exist. (NOTE 5)
SUBSCRIPTION_NOT_FOUND	404 Not Found	Indicates that the modification or deletion of subscription to events has failed due to an application error when the subscription is not found in the PCF. (NOTE 6)
PDU_SESSION_NOT_AVAILABLE	500 Internal Server Error	The PCF failed in executing session binding. (NOTE 7)
NOTE 1: This application error is included in the response to the POST request (see subclauses 4.2.2.2 and 4.2.2.5) and to the PATCH request (see subclauses 4.2.3.2 and 4.2.3.5).		
NOTE 2: This application error is included in the response to the POST request (see subclause 4.2.2.2) and to the PATCH request (see subclause 4.2.3.2).		
NOTE 3: This application error is included in the response to the POST request (see subclause 4.2.2.5) and to the PATCH request (see subclause 4.2.3.5).		
NOTE 4: This application error is included in the response to the POST request (see subclause 4.2.2.8), and to the PATCH request (see subclause 4.2.3.9).		
NOTE 5: This application error is included in the responses to the POST, GET, PATCH, PUT and DELETE requests.		
NOTE 6: This application error is included in the response to the PATCH request (see subclause 4.2.3.2), to the PUT request (see subclause 4.2.6.2) and to the DELETE request (see subclause 4.2.6.7).		
NOTE 7: This application error is included in the response to the POST request (see subclauses 4.2.2.2).		

5.8 Feature negotiation

The optional features in table 5.8-1 are defined for the Npcf_PolicyAuthorization API. They shall be negotiated using the extensibility mechanism defined in subclause 6.6 of 3GPP TS 29.500 [5].

Table 5.8-1: Supported Features

Feature number	Feature Name	Description
0	Sponsored Connectivity	Indicates support of sponsored data connectivity. If the PCF supports this feature, the AF may provide sponsored data connectivity to the SUPI.
1	Influence on Traffic Routing	Indicates support of Application Function influence on traffic routing. If the PCF supports this feature, the AF may influence SMF routing to applications or subscribe to notifications of UP path management for the traffic flows of an active PDU session.
2	NetLoc	Indicates the support of access network information reporting.

Annex A (normative): OpenAPI specification

A.1 General

The present Annex contains an OpenAPI [11] specification of HTTP messages and content bodies used by the Npcf_PolicyAuthorization API.

In case of conflicts between the main body of the present document and the present Annex, the information in the main body shall be applicable.

A.2 Npcf_PolicyAuthorization API

Editor's note: Agreements on failure cases and consolidation of agreed datatypes need to be reflected in the OpenAPI definition.

```

openapi: 3.0.0
info:
  title: "Npcf_PolicyAuthorization Service API"
  version: "1.preR15.0.0"
  description: "This is the Policy Authorization Service"

externalDocs:
  description: "3GPP TS 29.514 V0.5.0, 5G System; Policy Authorization Service"
  url: 'http://www.3gpp.org/ftp/Specs/archive/29_series/29.514/'

servers:
  - url: https://{apiRoot}/npcf-policyauthorization/v1
    variables:
      apiRoot:
        default: virtserver.3gpp5gc-sbi.com
        description: "apiRoot as defined in subclause 4.4 of 3GPP TS 29.501 excluding the https://"
part"
paths:
  /app-sessions:
    post:
      summary: Creates a new Individual Application Session Context resource
      operationId: PostAppSessions
      tags:
        - Individual Application Session Context (Collection)
      requestBody:
        description: Contains the information for the creation the resource
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/AppSessionContextReqData'
      responses:
        '201':
          description: Successful creation of the resource
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/AppSessionContext'
        '303':
          $ref: 'TS29571_CommonData.yaml#/components/schemas/responses/303'
        '400':
          description: Bad request
          content:
            application/problem+json:
              schema:
                $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
        '403':
          description: Forbidden
          content:
            application/problem+json:

```

```

    schema:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
  '404':
    description: Not Found
    content:
      application/problem+json:
        schema:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
  '411':
    description: Length Required
    content:
      application/problem+json:
        schema:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
  '415':
    description: Unsupported Media Type
    content:
      application/problem+json:
        schema:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
  '500':
    description: Internal Server Error
    content:
      application/problem+json:
        schema:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
  '503':
    description: Service Unavailable
    content:
      application/problem+json:
        schema:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
callbacks:
  terminationRequest:
    '{$request.body#/notifUri}/terminate':
      post:
        requestBody:
          description: Request of the termination of the Individual Application Session
Context
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/TerminationInfo'
  responses:
    '204':
      description: The receipt of the notification is acknowledged.
    '400':
      description: Bad request
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '404':
      description: Not Found
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '411':
      description: Length Required
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '415':
      description: Unsupported Media Type
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '500':
      description: Internal Server Error
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '503':
      description: Service Unavailable

```

```

        content:
          application/problem+json:
            schema:
              $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
eventNotification:
  '{$request.body#/evSubsc/notifUri}/notify':
    post:
      requestBody:
        description: Notification of an event occurrence in the PCF.
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/EventsNotification'
      responses:
        '204':
          description: The receipt of the notification is acknowledged
        '400':
          description: Bad request
          content:
            application/problem+json:
              schema:
                $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
        '404':
          description: Not Found
          content:
            application/problem+json:
              schema:
                $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
        '411':
          description: Length Required
          content:
            application/problem+json:
              schema:
                $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
        '415':
          description: Unsupported Media Type
          content:
            application/problem+json:
              schema:
                $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
        '500':
          description: Internal Server Error
          content:
            application/problem+json:
              schema:
                $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
        '503':
          description: Service Unavailable
          content:
            application/problem+json:
              schema:
                $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
/app-sessions/{appSessionId}:
  get:
    summary: "Reads an existing Individual Application Session Context"
    operationId: GetAppSession
    tags:
      - Individual Application Session Context resource
    parameters:
      - name: appSessionId
        description: string identifying the resource
        in: path
        required: true
        schema:
          type: string
    responses:
      '200':
        description: A representation of the resource is returned.
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/AppSessionContext'
      '400':
        description: Bad request
        content:
          application/problem+json:
            schema:
              $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'

```

```

'404':
  description: Not Found
  content:
    application/problem+json:
      schema:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
'500':
  description: Internal Server Error
  content:
    application/problem+json:
      schema:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
'503':
  description: Service Unavailable
  content:
    application/problem+json:
      schema:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
patch:
  summary: "Modifies an existing Individual Application Session Context"
  operationId: ModAppSession
  tags:
    - Individual Application Session Context resource
  parameters:
    - name: appSessionId
      description: string identifying the resource
      in: path
      required: true
      schema:
        type: string
  requestBody:
    description: modification of the resource.
    required: true
    content:
      application/merge-patch+json:
        schema:
          $ref: '#/components/schemas/AppSessionContextUpdateData'
  responses:
    '200':
      description: successful modification of the resource and a representation of that resource
      is returned
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/AppSessionContext'
    '204':
      description: The successful modification
    '400':
      description: Bad request
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '403':
      description: Forbidden
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '404':
      description: Not Found
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '409':
      description: Conflict
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '411':
      description: Length Required
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '415':

```

```

description: Unsupported Media Type
content:
  application/problem+json:
    schema:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
'500':
description: Internal Server Error
content:
  application/problem+json:
    schema:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
'503':
description: Service Unavailable
content:
  application/problem+json:
    schema:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
callbacks:
eventNotification:
  '{$request.body#/evSubsc/notifUri}/notify':
  post:
    requestBody:
      description: Notification of an event occurrence in the PCF.
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/EventsNotification'
    responses:
      '204':
        description: The receipt of the notification is acknowledged
      '400':
        description: Bad request
        content:
          application/problem+json:
            schema:
              $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
      '404':
        description: Not Found
        content:
          application/problem+json:
            schema:
              $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
      '411':
        description: Length Required
        content:
          application/problem+json:
            schema:
              $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
      '415':
        description: Unsupported Media Type
        content:
          application/problem+json:
            schema:
              $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
      '500':
        description: Internal Server Error
        content:
          application/problem+json:
            schema:
              $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
      '503':
        description: Service Unavailable
        content:
          application/problem+json:
            schema:
              $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
#
#
/app-sessions/{appSessionId}/delete:
  post:
    summary: "Deletes an existing Individual Application Session Context"
    operationId: DeleteAppSession
    tags:
      - Individual Application Session Context resource
    parameters:
      - name: appSessionId
        description: string identifying the Individual Application Session Context resource
        in: path

```



```

        required: true
        schema:
          type: string
      requestBody:
        description: deletion of the Individual Application Session Context resource, req
notification
        required: false
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/EventsSubscReqData'
      responses:
        '200':
          description: The deletion of the resource is confirmed and a resource is returned
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/AppSessionContext'
        '204':
          description: The deletion is confirmed without returning additional data.
        '400':
          description: Bad request
          content:
            application/problem+json:
              schema:
                $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
        '404':
          description: Not Found
          content:
            application/problem+json:
              schema:
                $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
        '411':
          description: Length Required
          content:
            application/problem+json:
              schema:
                $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
        '415':
          description: Unsupported Media Type
          content:
            application/problem+json:
              schema:
                $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
        '500':
          description: Internal Server Error
          content:
            application/problem+json:
              schema:
                $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
        '503':
          description: Service Unavailable
          content:
            application/problem+json:
              schema:
                $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
#
/app-sessions/{appSessionId}/events-subscription:
  put:
    summary: "creates or modifies an Events Subscription subresource"
    operationId: updateEventsSubsc
    tags:
      - Individual Events Subscription resource
    parameters:
      - name: appSessionId
        description: string identifying the Events Subscription resource
        in: path
        required: true
        schema:
          type: string
    requestBody:
      description: Creation or modification of an Events Subscription resource.
      required: true
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/EventsSubscReqData'
    responses:

```

```

'201':
  description: The creation of the Events Subscription resource is confirmed and its
representation is returned.
  content:
    application/json:
      schema:
        anyOf:
          - $ref: '#/components/schemas/EventsSubscReqData'
          - $ref: '#/components/schemas/EventsNotification'
'200':
  description: The modification of the of the Events Subscription resource is confirmed its
representation is returned.
  content:
    application/json:
      schema:
        anyOf:
          - $ref: '#/components/schemas/EventsSubscReqData'
          - $ref: '#/components/schemas/EventsNotification'
'204':
  description: The modification of the of the Events Subscription subresource is confirmed
without returning additional data.
'400':
  description: Bad request
  content:
    application/problem+json:
      schema:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
'403':
  description: Forbidden
  content:
    application/problem+json:
      schema:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
'404':
  description: Not Found
  content:
    application/problem+json:
      schema:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
'409':
  description: Conflict
  content:
    application/problem+json:
      schema:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
'411':
  description: Length Required
  content:
    application/problem+json:
      schema:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
'415':
  description: Unsupported Media Type
  content:
    application/problem+json:
      schema:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
'500':
  description: Internal Server Error
  content:
    application/problem+json:
      schema:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
'503':
  description: Service Unavailable
  content:
    application/problem+json:
      schema:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
callbacks:
  eventNotification:
    '{$request.body#/notifUri}/notify':
      post:
        requestBody:
          description: Contains the information for the notification of an event occurrence in
the PCF.
          content:
            application/json:

```

```

    schema:
      $ref: '#/components/schemas/EventsNotification'
  responses:
    '204':
      description: The receipt of the notification is acknowledged.
    '400':
      description: Bad request
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '404':
      description: Not Found
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '411':
      description: Length Required
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '415':
      description: Unsupported Media Type
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '500':
      description: Internal Server Error
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '503':
      description: Service Unavailable
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
  delete:
    summary: deletes the Events Subscription subresource
    operationId: DeleteEventsSubsc
    tags:
      - Individual Events Subscription resource
    parameters:
      - name: appSessionId
        description: string identifying the Individual Application Session Context resource
        in: path
        required: true
        schema:
          type: string
    responses:
      '204':
        description: The deletion of the of the Events Subscription sub-resource is confirmed
without returning additional data.
      '400':
        description: Bad request
        content:
          application/problem+json:
            schema:
              $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
      '403':
        description: Forbidden
        content:
          application/problem+json:
            schema:
              $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
      '404':
        description: Not Found
        content:
          application/problem+json:
            schema:
              $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
      '500':
        description: Internal Server Error
        content:

```

```

    application/problem+json:
      schema:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
  '503':
    description: Service Unavailable
    content:
      application/problem+json:
        schema:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
components:
  schemas:
    AppSessionContext:
      description: Represents an Individual Application Session Context resource.
      type: object
      properties:
        ascReqData:
          $ref: '#/components/schemas/AppSessionContextReqData'
        ascRespData:
          $ref: '#/components/schemas/AppSessionContextRespData'
        evsNotif:
          $ref: '#/components/schemas/EventsNotification'
    AppSessionContextReqData:
      description: Identifies the service requirements of an Individual Application Session Context.
      type: object
      required:
        - notifUri
      properties:
        afAppId:
          $ref: '#/components/schemas/AfAppId'
        afChargId:
          $ref: '#/components/schemas/AfChargingId'
        afRoutReq:
          $ref: '#/components/schemas/AfRoutingRequirement'
        aspId:
          $ref: '#/components/schemas/AspId'
        bdtRefId:
          $ref: 'TS29122_CommonData.yaml#/components/schemas/BdtReferenceId'
        dnn:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Dnn'
        evSubsc:
          $ref: '#/components/schemas/EventsSubscReqData'
        medComponents:
          type: object
          additionalProperties:
            $ref: '#/components/schemas/MediaComponent'
        notifUri:
          $ref: 'TS29122_CommonData.yaml#/components/schemas/Link'
        sliceInfo:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
        sponId:
          $ref: '#/components/schemas/SponId'
        sponStatus:
          $ref: '#/components/schemas/SponsoringStatus'
        supi:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Supi'
        supportedFeatures:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/SupportedFeatures'
        ueIpv4:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv4Addr'
        ueIpv6:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv6Addr'
        ueMac:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Mac48'
    AppSessionContextRespData:
      description: Describes the authorization data of an Individual Application Session Context
      created by the PCF.
      type: object
      properties:
        servAuthInfo:
          $ref: '#/components/schemas/ServAuthInfo'
    AppSessionContextUpdateData:
      description: Identifies the modifications to an Individual Application Session Context and may
      include the modifications to the sub-resource Events Subscription.
      type: object
      properties:
        afAppId:
          $ref: '#/components/schemas/AfAppId'
        afRoutReq:

```

```

    $ref: '#/components/schemas/AfRoutingRequirement'
  aspId:
    $ref: '#/components/scemas/AspId'
  bdtRefId:
    $ref: 'TS29122_CommonData.yaml#/components/schemas/BdtReferenceId'
  evSubsc:
    $ref: '#/components/schemas/EventsSubscReqData'
  medComponents:
    type: object
    additionalProperties:
      $ref: '#/components/schemas/MediaComponent'
  sponId:
    $ref: '#/components/schemas/SponId'
  sponStatus:
    $ref: '#/components/schemas/SponsoringStatus'
EventsSubscReqData:
  description: Identifies the events the application subscribes to.
  type: object
  required:
    - events
    - notifUri
  properties:
    events:
      type: array
      items:
        $ref: '#/components/schemas/AfEventSubscription'
    notifUri:
      $ref: 'TS29122_CommonData.yaml#/components/schemas/Link'
    reqAni:
      $ref: '#/components/schemas/RequiredAccessInfo'
    usgThres:
      $ref: 'TS29122_CommonData.yaml#/components/schemas/UsageThreshold'
MediaComponent:
  description: Identifies a media component.
  type: object
  required:
    - medCompN
  properties:
    afAppId:
      $ref: '#/components/schemas/AfAppId'
    afRoutReq:
      $ref: '#/components/schemas/AfRoutingRequirement'
    codecs:
      type: array
      items:
        $ref: '#/components/schemas/CodecData'
    fStatus:
      $ref: '#/components/schemas/FlowStatus'
    marBwDl:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/BitRate'
    marBwUl:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/BitRate'
    medCompN:
      type: integer
    medSubComps:
      type: object
      additionalProperties:
        $ref: '#/components/schemas/MediaComponent'
    medType:
      $ref: '#/components/schemas/MediaType'
    mirBwDl:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/BitRate'
    mirBwUl:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/BitRate'
    resPrio:
      $ref: '#/components/schemas/ReservPriority'
MediaSubComponent:
  description: Identifies a media subcomponent
  type: object
  required:
    - fNum
  properties:
    ethfDescs:
      type: array
      items:
        $ref: '#/components/schemas/EthFlowDescription'
    fNum:
      type: integer

```

```

fDescs:
  type: array
  items:
    $ref: '#/components/schemas/FlowDescription'
fStatus:
  $ref: '#/components/schemas/FlowStatus'
marBwDl:
  $ref: 'TS29571_CommonData.yaml#/components/schemas/BitRate'
marBwUl:
  $ref: 'TS29571_CommonData.yaml#/components/schemas/BitRate'
tosTrCL:
  $ref: '#/components/schemas/ToSTrafficClass'
EventsNotification:
  description: describes a notification of a matched event
  type: object
  required:
    - evSubsUri
    - evNotif
  properties:
    accessType:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/AccessType'
    anChargAddr:
      $ref: '#/components/schemas/AccessNetChargingAddress'
    anChargIds:
      type: array
      items:
        $ref: '#/components/schemas/AccessNetChargingIdentifier'
    anGwAddr:
      $ref: '#/components/schemas/AnGwAddress'
    evSubsUri:
      $ref: 'TS29122_CommonData.yaml#/components/schemas/Link'
    evNotif:
      type: array
      items:
        $ref: '#/components/schemas/AfEventNotification'
    netLocAccSupp:
      $ref: '#/components/schemas/NetLocAccSupp'
    plmnCcNc:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
    plmnId:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
    ratType:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/ratType'
    ueLoc:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/UserLocation'
    ueLocTime:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
    useTimeZone:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/TimeZone'
    usgRep:
      $ref: 'TS29122_CommonData.yaml#/components/schemas/AccumulatedUsage'
AfEventSubscription:
  description: describes the event information delivered in the subscription
  type: object
  required:
    - event
  properties:
    dnaiChgType:
      $ref: 'TS29508_CommonData.yam#/components/scemas/DnaiChangeType'
    event:
      $ref: '#/components/schemas/AfEvent'
    notifMethod:
      $ref: '#/components/schemas/AfNotifMethod'
AfEventNotification:
  description: describes the event information delivered in the notification
  type: object
  required:
    - event
  properties:
    event:
      $ref: '#/components/schemas/AfEvent'
    flows:
      type: array
      items:
        $ref: '#/components/schemas/Flows'
    notifType:
      $ref: '#/components/schemas/QosNotifType'
TerminationInfo:

```

```

    description: indicates the cause for requesting the deletion of the Individual Application
Session Context resource
  type: object
  required:
    - termCause
    - resUri
  properties:
    termCause:
      $ref: '#/components/schemas/TerminationCause'
    resUri:
      $ref: 'TS29122_CommonData.yaml#/components/schemas/Link'
AfRoutingRequirement:
  description: describes the event information delivered in the subscription
  type: object
  properties:
    appReloc:
      type: boolean
    routeToLocs:
      type: array
      items:
        $ref: '#/components/schemas/RouteToLocation'
    spVal:
      $ref: '#/components/schemas/SpatialValidity'
    startTime:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
    stopTime:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
RouteToLocation:
  description: describes the route to an Application location
  type: object
  required:
    - dnai
  properties:
    dnai:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/Dnai'
    routeInfo:
      $ref: '#/components/schemas/RouteInformation'
    routeProfId:
      type: string
RouteInformation:
  description: describes explicitly the route to an Application location
  type: object
  required:
    - ipv6Addr
    - portNumber
  properties:
    ipv6Addr:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv6Addr'
    portNumber:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/UInteger'
SpatialValidity:
  description: describes explicitly the route to an Application location
  type: object
  properties:
    praIds:
      type: array
      items:
        type: string
    praElements:
      type: array
      items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/PraElement'
AccessNetChargingAddress:
  description: describes the network entity within the access network performing charging
  type: object
  properties:
    anChargIpv4Addr:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv4Addr'
    anChargIpv6Addr:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv6Addr'
AccessNetChargingIdentifier:
  description: describes the access network charging identifier
  type: object
  properties:
    anChargIdValue:
      type: string
    flows:
      type: array

```

```

        items:
          $ref: '#/components/schemas/Flows'
AnGwAddress:
  description: describes the address of the access network gateway control node
  type: object
  properties:
    anGwIpv4Addr:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv4Addr'
    anGwIpv6Addr:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv6Addr'
Flows:
  description: Identifies the flows
  type: object
  properties:
    fNums:
      type: array
      items:
        type: integer
    medCompN:
      type: integer
EthFlowDescription:
  description: Identifies an Ethernet flow
  type: object
  properties:
    destMacAddr:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/Mac48'
#
  ethType:
    type: string
  fDesc:
    $ref: '#/components/schemas/FlowDescription'
  fDir:
    $ref: 'TS29512_CommonData.yaml#/components/schemas/FlowDirection'
  sourceMacAddr:
    $ref: 'TS29571_CommonData.yaml#/components/schemas/Mac48'
  vlanTags:
    type: string
#
# SIMPLE DATA TYPES
#
AfChargingId:
  description: Contains an AF application identifier.
  type: string
AfAppId:
  description: Contains an AF application identifier.
  type: string
AspId:
  description: Contains an identity of an application service provider.
  type: string
CodecData:
  description: Contains codec related information.
  type: string
FlowDescription:
  description: Defines a packet filter of an IP flow.
  type: string
NetLocAccSupp:
  description: Indication of whether the access network supports access network information
reporting.
  type: boolean
SponId:
  description: Contains an identity of a sponsor.
  type: string
#
# ENUMERATIONS DATA TYPES
#
MediaType:
  anyOf:
    - type: string
      enum:
        - AUDIO
        - VIDEO
        - DATA
        - APPLICATION
        - CONTROL
        - TEXT
        - MESSAGE
        - OTHER
    - type: string

```



```
#
  ReservPriority:
    anyOf:
      - type: string
        enum:
          - PRIO_1
          - PRIO_2
          - PRIO_3
          - PRIO_4
          - PRIO_5
          - PRIO_6
          - PRIO_7
          - PRIO_8
          - PRIO_9
          - PRIO_10
          - PRIO_11
          - PRIO_12
          - PRIO_13
          - PRIO_14
          - PRIO_15
          - PRIO_16
      - type: string
#
  ServAuthInfo:
    anyOf:
      - type: string
        enum:
          - TP_NOT_KNOWN
          - TP_EXPIRED
          - TP_NOT_YET_OCURRED
          - UNAUTH_TRAFFIC_ROUTING_REQ
      - type: string
#
  SponsoringStatus:
    anyOf:
      - type: string
        enum:
          - SPONSOR_DISABLED
          - SPONSOR_ENABLED
      - type: string
#
  AfEvent:
    anyOf:
      - type: string
        enum:
          - ACTIVITY
          - ANI_REPORT
          - CHARGING_CORRELATION
          - DNAI_CHG
          - FAILED_RESOURCES_ALLOCATION
          - PLMN_CHG
          - QOS_NOTIFICATION_CONTROL
          - ROUT_REQ_STATUS_CHG
          - USAGE_REPORT
      - type: string
#
  AfNotifMethod:
    anyOf:
      - type: string
        enum:
          - EVENT_DETECTION
          - ONE_TIME
      - type: string
#
  QosNotifType:
    anyOf:
      - type: string
        enum:
          - FULFILLED
          - NOT_FULFILLED
      - type: string
#
  TerminationCause:
    anyOf:
      - type: string
        enum:
          - ALL_SDF_DEACTIVATION
          - PDU_SESSION_TERMINATION
```

```
- type: string
#
  RequiredAccessInfo:
    anyOf:
      - type: string
      enum:
        - USER_LOCATION
        - MS_TIME_ZONE
      - type: string
# Additional types FFS
  FlowStatus:
    type: string
  ToSTrafficClass:
    type: string
```

Annex B (informative): Change history

Change history						
Date	TSG #	TSG Doc.	CR	Rev	Cat	Subject/Comment
2017-10						TS skeleton of Policy Authorization Service specification
2017-03	CT3#92					Inclusion of pCRs agreed during CT3#92
2018-01	CT3#94					Inclusion of documents agreed in CT3#94: C3-180036, C3-180038, C3-180212, C3-180213, C3-180214, C3-180217, C3-180218, C3-180243, C3-180313, C3-180314, C3-180315, C3-180316.
2018-03	CT3#95					Inclusion of documents agreed in CT3#95: C3-181229, C3-181338, C3-181231, C3-181232, C3-181339, C3-181323
2018-04	CT3#96					Inclusion of documents agreed in CT3#96: C3-182057, C3-182333, C3-182235, C3-182334, C3-182474, C3-182336, C3-182337, C3-182338, C3-182339, C3-182245, C3-182475, C3-182247, C3-182248, C3-182249, C3-182250, C3-182251
2018-06	CT3#97					Inclusion of documents agreed in CT3#97: C3-183220, C3-183222, C3-183230, C3-183233, C3-183234, C3-183239, C3-183281, C3-183300, C3-183301, C3-183517, C3-183518, C3-183520, C3-183521, C3-183522, C3-183523, C3-183524, C3-183525, C3-183526, C3-183577, C3-183579, C3-183580, C3-183581, C3-183582, C3-183583, C3-183584, C3-183585, C3-183586, C3-183587, C3-183588, C3-183589, C3-183590, C3-183591, C3-183592, C3-183820, C3-183821, C3-183822, C3-183879, C3-183882.
2018-06	CT#80					TS sent to plenary for approval
2018-06	CT#80					TS approved by plenary